

Non-Acetone

NSI-163



F : Highly flammable



Xi : Irritant

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name : Non-Acetone
Identification of the product : Liquid.
Type of product : Solvent.
Use : For professional use only.
Company identification : NAIL SYSTEMS INTERNATIONAL
 2 Union Hill Road
 W. Conshohocken, PA 19428 UNITED STATES
 Tel. (610) 825-1524
Emergency phone nr : Infotrac (800) 535-5053 - Outside USA (352) 323-3500

2 HAZARDS IDENTIFICATION

Risk Phrases : Irritating to eyes.
 Highly flammable.
Dangerous product : In use, may form flammable/explosive vapour-air mixture.
Primary route of exposure : Eyes contact.
 Vapours inhalation.
Symptoms relating to use
 - **Inhalation** : Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.
 - **Skin contact** : Prolonged or repeated contact may cause skin to become dry or cracked.
 - **Eye contact** : Redness, pain. Blurred vision. Burning sensation.
 - **Ingestion** : Abdominal pain, nausea.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Preparation : Preparation.
Components : This product is hazardous.

Substance name	Contents	CAS No	EC No	Annex No	Classification
MEK	: >= 50 < 60 %	78-93-3	201-159-0	606-002-00-3	F; R11 R66 R67 Xi; R36
ISOPROPYL ALCOHOL	: > 20 < 30 %	67-63-0	200-661-7	603-117-00-0	F; R11 R67 Xi; R36
ETHYL ACETATE	: > 10 < 15 %	141-78-6	205-500-4	607-022-00-5	F; R11 R66 R67 Xi; R36
WATER (AQUA)	: > 5 < 10 %	7732-18-5	231-791-2	----	

Non-Acetone

NSI-163

4 FIRST AID MEASURES

First aid measures

- **Inhalation** : Assure fresh air breathing. Inhalation of vapour can cause breathing difficulties. Obtain medical attention.
- **Skin contact** : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- **Eye contact** : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- **Ingestion** : Rinse mouth. Spit. If swallowed, seek medical advice immediately and show this container or label.

5 FIRE-FIGHTING MEASURES

- Flammable class** : This product is flammable.
- Prevention** : No naked lights. No smoking.
- Extinguishing media** : Water spray. Foam. Dry chemical. Carbon dioxide.
- Surrounding fires** : Use water spray or fog for cooling exposed containers.
- Protection against fire** : Do not enter fire area without proper protective equipment, including respiratory protection.
- Special procedures** : Exercise caution when fighting any chemical fire.

6 ACCIDENTAL RELEASE MEASURES

- Personal precautions** : No naked lights. No smoking. Evacuate and limit access. Equip cleanup crew with proper protection.
- Environmental precautions** : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.
- Clean up methods** : Clean up any spills as soon as possible, using an absorbent material to collect it. Use suitable disposal containers.

7 HANDLING AND STORAGE

- General** : No naked lights. No smoking.
- Precautions in handling and storage** : Good ventilation of the workplace required.
- Technical protective measures** : Use only non-sparking tools. Provide proper grounding.
- Storage** : Keep in fireproof place. Keep container closed when not in use. Use special care to avoid static electric charges.
- Storage - away from** : Heat sources.
- Handling** : Handle in accordance with good industrial hygiene and safety procedures. Ensure prompt removal from eyes, skin and clothing. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Personal protection**
- **Respiratory protection** : Where excessive vapour may result, wear approved mask.
- **Hand protection** : Gloves.
- **Skin protection** : Protective clothing not absolutely necessary.

Non-Acetone

NSI-163

8 EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- Eye protection : Chemical goggles or safety glasses.
- Ingestion : When using, do not eat, drink or smoke.
- Industrial hygiene : Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations.
- Occupational Exposure Limits : Butanone : ILV (EU) - 8 H - [mg/m³] : 600
Butanone : ILV (EU) - 8 H - [ppm] : 200
Butanone : ILV (EU) - 15 min - [mg/m³] : 900
Butanone : ILV (EU) - 15 min - [ppm] : 300

9 PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at 20 °C : Liquid.
- Colour : Clear.
- Odour : Solvent.
- Boiling point [°C] : 79
- Vapour pressure mm/Hg : @ 20 deg C 42
- Viscosity : Like that of water.
- Solubility in water : Complete.
- Flash point [°C] : TCC -6.7
- Flammability range [vol% in air] : LEL: 0.018 UEL:0.1
- Auto-ignition temperature [°C] : 399
- Other data : Specific Gravity (water=1) 0.796
Relative Evaporation Rate (water=1) < 1

10 STABILITY AND REACTIVITY

- Stability and reactivity : Stable.
- Hazardous decomposition products : None under normal conditions.
- Hazardous properties : Vapour mixes readily with air, forming explosive mixtures.
- Conditions to avoid : Open flame.
Sparks.
Overheating.

11 TOXICOLOGICAL INFORMATION

- Toxicity information : No data available.
- Rat oral LD50 [mg/kg] : Ingredient Data:
MEK - 3400 mg/kg
Isopropyl Alcohol - 5840 mg/kg
- Rat inhalation LC50 [ppm] : Ingredient Data:
MEK 8,000ppm/4H
Isopropyl Alcohol 22,500ppm/4H



SAFETY DATA SHEET

Page : 4

Revised edition no : 2

Date : 4 / 28 / 2008

Supersedes : 3 / 4 / 2008

Non-Acetone**NSI-163**

12 ECOLOGICAL INFORMATION

Ecological effects information : No data available.
LC50-96 Hour - fish [mg/l] : No data available.
48 Hour-EC50 - Daphnia magna [mg/l] : No data available.
IC50 72h Algae [mg/l] : No data available.

13 DISPOSAL CONSIDERATIONS

General : Dispose in a safe manner in accordance with local/national regulations.

14 TRANSPORT INFORMATION

Proper shipping name : UN1263 PAINT RELATED MATERIAL, 3, II
UN No. : 1263
H.I. nr : 33
ADR/RID : Group : II
Special provision : 640D
Class : 3

Substance name	Contents	CAS No	EC No	Annex No	Classification
		128-80-3	204-909-5	-----	

15 REGULATORY INFORMATION

Symbol(s) : Xi : Irritant
F : Highly flammable

R Phrase(s) : R11 : Highly flammable.
R36 : Irritating to eyes.
R66 : Repeated exposure may cause skin dryness or cracking.
R67 : Vapours may cause drowsiness and dizziness.

S Phrase(s) : S16 : Keep away from sources of ignition - No smoking.
S24 : Avoid contact with skin.
S33 : Take precautionary measures against static discharges.
S35 : This material and its container must be disposed of in a safe way.

16 OTHER INFORMATION

Revision : Revision - See : *

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

For EU Regulatory Inquiries please contact:
FSE International NV/SA
9 Rue du Moniteur-B-1000
Brussels, Belgium
011 322 277 07 70

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with



SAFETY DATA SHEET

Page : 5

Revised edition no : 2

Date : 4 / 28 / 2008

Supersedes : 3 / 4 / 2008

Non-Acetone

NSI-163

the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document