MATERIAL SAFETY DATA SHEET

Page 1 of 8

MSDS-007

Prep	ared to OSHA,	ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standard	s N	MSDS Revision: 2.0	MSDS	Revision Date	: 07/15/2008
		1. PRODUCT ID	<u>ENT</u>	TFICATION			
1.1	Product Name:						
	ARTIFICIA	AL NAIL REMOVER					
1.2	Chemical Name:						
	ACETONE SOL	UTION					
1.3	Synonyms:						
1.4	NA Trade Names:						
1.4	AL601, AL604,	AL606					
1.5	Product Use:						
	COSMETIC US	E ONLY					
1.6	Manufacturer's Na						
4.7	OPI PRODUCT	•					
1.7	Manufacturer's Ac	ordess: Dy Street, No. Hollywood, CA 91605 USA					
1.8	Emergency Phone						
	9 ,	: +1 (703) 527-3887 / +1 (800) 424-9300					
1.9	Business Phone:						
	+1 (818) 759-2	2400 / +1 (800) 341-9999					
		2. HAZARD IDI	ENTI	FICATION			
2.1	Hazard Identificati	ion:					
		is classified as a HAZARDOUS SUBSTANCE and (2004) and ADG Code (Australia). Flammable Liquic		ANGEROUS GOODS	according t	o the classifi	cation criteria of
2.2	Routes of Entry:	Inhalation: YES		Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure	- 9:					
	INGESTION:	If product is swallowed, may cause nausea, vomit	ing a	nd/or diarrhea and	central nervo	us system dep	oression.
	SKIN & EYES:	Irritating to the eyes. Symptoms of overexposurirritating to skin in some sensitive individuals, espe					itering. May be
	INHALATION:						
		Symptoms of overexposure can include coughing vapors exceeding the levels listed in Section 2 (
		system depression (e.g., drowsiness, dizziness, hec				,	
2.4	Symptoms of Over	•					
	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.						
2.5	Acute Health Effec	•					
		rate irritation to eyes and skin near affected areas idaches and nausea.	. Add	ditionally, high con	centrations of	vapors can c	ause drowsiness,
2.6	Chronic Health Eff						
	None known; individuals.	however, methylparaben, contained in very smal	i qua	ntities in this produ	ct, may be m	ild allergens	to some sensitive
2.7	Target Organs:						
	Eyes, skin and	d respiratory system.					
		; $ND = Not Determined$; $NE = Not Established$; $C = Cotons$	_				
NOT	E: all WHMIS re	quired information is included. It is located in appro	priate	e sections based or	n the ANSI Z40	0.1-2004 forma	at.

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-007

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008															
			3 CO	MPOSITIO	N O INCE	EDIEN	IT INIE		A A TI) NI					
			3. CO		IN & INGN	LEDIEN	I IINI	OKA			2TIMI	IN AIR	(ma/n	n3\	
						ACGIH		NOHSC EXPOSURE LIMITS			OSHA				
							ppm			ppm	1	ppm			OTHER
	CHEMICAL NA	ME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
ACET		(0)	67-64-1	AL3150000	200-662-2	≤ 95.0	500	750	500	1000	NF	1000	1000	NE	
ETHYL	HEXYL PALMITA	TE	29806-73-3	NA	249-862-1	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
PERSE OIL	A GRATISSIMA	(AVOCADO)	8024-32-6	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
METH	HEXYL OXYCINNAMAT		5466-77-3	NA	226-775-7	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
-	ONDSIA CHINEI DBA) SEED OIL	NSIS	90045-98-0	NY9262700	296-292-4	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
FRAG	RANCE (PARFU/	M)	NA	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
LECIT	HIN		8002-43-5	OG7565000	297-639-2	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CAPR	IC/CAPRILIC TR	IGLYCERIDE	65381-09-1	NA	265-724-3	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ALCO	HOL		64-17-5	KQ6300000	200-578-6	< 1.0	1000	3000	1000	NF	NF	1000	3000	NE	
ASCC	RBYL PALMITAT	E	137-66-6	CI7671040	205-305-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
GLYC	ERYL STEARATE		31566-31-1	RG1925000	250-705-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
OLEIC	CACID		112-80-1	RG22750000	204-007-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
LIMO	NENE		5989-27-5	GW6360000	227-813-5	< 1.0	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
METH	YLPARABEN		99-76-3	DH2450000	202-785-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
HEXY	L CINNAMAL		101-86-0	GD6560000	202-983-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
TOCC	PHEROL		59-02-9	DJ2900000	200-412-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 42	090 (BLUE 1)		3844-45-9	BQ4725000	223-339-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
				4. F	IRST AID I	MEASI	JRES								
INGESTION: Ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material vingested and the amount of the substance that was swallowed. EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least minutes. If irritation occurs, contact a physician. SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. INHALATION: Remove victim to fresh air at once.						entact the terial was at least 15									
4.2 Medical Conditions Aggravated by Exposure:						1									
	None known.	-									DILIT	V			
								_	FLAN REAC						3
												- CIII	DAAF	NIT	0
								-			IVE	שטו	PME	IN I	Α
									EYES						

$0.9 \cdot 1$

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-007

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008

5. FIREFIGHTING MEASURES

2.6

5.1 Flashpoint & Method:

-17 °C (1.4 °F), Closed Cup

5.2 Autoignition Temperature:

869°F

5.3

5.6

5.4 Fire & Explosion Hazards:

Flammability Limits

WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.

Lower Explosive Limit (LEL):

5.5

CO₂, Halon, Dry Chemical, Foam


Firefighting Procedures:

HazChem Code: 2YE

Hazard Identification Number: 33

This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



12.8

Upper Explosive Limit (UEL):

6. ACCIDENTAL RELEASE MEASURES

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7.2 Storage & Handling:

> Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

Special Precautions:

Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. Store in original containers. Do not store where temperatures may exceed 120 °F.

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-007

Prep	ared to OSHA, ACC, ANSI, N	IOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008								
		8. EXPOSURE CONTROLS & PERSONAL PROTECTION								
8.1	Ventilation & Engineering Controls:									
		quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an ashbasin is available in case of exposure to eyes.								
3.2	Respiratory Protection:									
	protection authorized per	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.								
3.3	Eye Protection:									
		this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, e European Standard EN166.								
3.4	Hand Protection:									
		ped & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine r, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.								
3.5	Body Protection:									
	No special body protectio of Canada, the E.C. memb	n is required under typical circumstances of use and handling. If necessary, refer to appropriate standards per states, or U.S. OSHA.								
		A DUVALGAL A GUELLIGAL DROBERTIES								
		9. PHYSICAL & CHEMICAL PROPERTIES								
9.1	Density:	0.79								
0.2	Boiling Point:	56 °C (133 °F)								
.3	Melting Point:	NA NA								
9.4	Evaporation Rate:	NA								
9.5	Vapor Pressure:	NA								
9.6	Molecular Weight:	NE								
9.7	Appearance & Color:	Blue, translucent liquid with melon-like odor								
9.8	Odor Threshold:	ND								
9.9	Solubility:	Soluble in water.								
9.10	рН	NA NA								
9.11	Viscosity:	< 500 cPs								
9.12	Other Information:	NA								
		10. STABILITY & REACTIVITY								
10.1	Stability: Stable under ambient cond	ditions when stored properly (see Section 7, Storage and Handling).								
10.2	Hazardous Decomposition Products									
	If exposed to extremely h gases (e.g., CO, CO ₂).	igh temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide								
0.3	Hazardous Polymerization:									
		extremely high temperatures.								
10.4	Conditions to Avoid:									
		le with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), o assium hydroxide) and potassium t-butoxide.								
10.5	Incompatible Substances:									
	None known.									

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-007

Prep	ared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008
	11. TOXICOLOGICAL INFORMATION
11.1	Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity:
	See Section 2.5
11.3	Chronic Toxicity:
	See Section 2.6
11.4	Suspected Carcinogen: No
11.5	Reproductive Toxicity:
	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:
	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:
	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:
	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:
11.6	This product is not reported to cause reproductive effects in humans. Irritancy of Product:
11.0	See Section 2.3
11.7	Biological Exposure Indices:
	NE .
11.8	Physician Recommendations:
	Treat symptomatically.
	12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:
	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data
	available for the components of this product are not available.
12.2	Effects on Plants & Animals:
	There are no specific data available for this product.
12.3	Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.
	oreienposed aqualic lie.
	13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:
	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:
	U.S. EPA WASTE NUMBER: D001 (characteristic – ignitable)

0.91

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-007

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 07/15/2008

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGR and the CTDGR.

| 14.1 | 49 CFR (GND):
| CONSUMER COMMODITY, ORM-D
| UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L)

| 14.2 | IATA (AIR):
| CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)
| UN1090, ACETONE SOLUTIONS, 3, II (> 0.5 L)

| 14.3 | IMDG (OCN):
| UN1090, ACETONE SOLUTIONS, 3, II, LTD QTY (≤ 1.0 L)
| UN1090, ACETONE SOLUTIONS, 3, II, CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)

| 14.3 | IMDG (OCN):
| UN1090, ACETONE SOLUTIONS, 3, II, LTD QTY (≤ 1.0 L)
| UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L)



14.4 TDGR (Canadian GND):

MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L)

14.5 ADR/RID (EU):

UN1090, ACETONE SOLUTIONS, 3, II, ADR, LTD QTY (≤ 1.0 L)

UN1090, ACETONE SOLUTIONS, 3, II, ADR (> 1.0 L)

14.6 SCT (MEXICO)

UN1090, SOLUCIONES DE ACETONA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)

14.7 ADGR (AUS)

UN1090, ACETONE SOLUTIONS, 3, 2 $^{\circ}$ (b), LTD QTY (\leq 1.0 L)

15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

NA

15.2 SARA Threshold Planning Quantity:

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ):

Acetone: 5000 lbs.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



15.7 State Regulatory Information

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List Acetone **Delaware Air Quality Management List** Acetone Massachusetts Hazardous Substances List Acetone, Ethanol Minnesota Hazardous Substances List Acetone, Ethanol New York List of Hazardous Substances Acetone Pennsylvania Hazardous Substances List Acetone, Ethanol Washington Permissible Exposure Limits for Air Contaminants Acetone Wisconsin Hazardous Substances List Acetone

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC.

Acetone: Highly Flammable (F+). R: 11-36-66-67 – Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. S: 9-16-23-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Take precautionary measures against static discharges. HAZCHEM CODE: 2[Y]E. Poisons Schedule Number: S5



+1 (310) 370-3600 phone

+1 (310) 370-5700 fax http://www.shipmate.com

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-007

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 07/15/2008 16. OTHER INFORMATION 16.1 Other Information: EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: Please see last page of this MSDS. 16.3 This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: 16.4 OPI Products, Inc. 13034 Saticoy Street $O \cdot P \cdot I$ No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/ Prepared by: ShipMate, Inc. P.O. Box 787 780 Buckaroo Trail Suite D Sisters, OR 97759

Training & Consulting

$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-007

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 07/15/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
TLV Threshold Limit Value				
OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person							
					receives			
	compre	ssions a	nd bre	eathing to d	circulate bl	ood and p	rovide	
	oxygen	to the b	ody.					


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	1 Slight Hazard			
2 Moderate Hazard				
3	Severe Hazard			
4	Extreme Hazard			



PERSONAL PROTECTION RATINGS:







OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE Not Established	
ND Not Determined	
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Minimum temperature required to initiate combu-			
Temperature	in air with no other source of ignition		
LEL Lower Explosive Limit - lowest percent of vapor in air,			
	volume, that will explode or ignite in the presence of		
	an ignition source		
UEL	Upper Explosive Limit - highest percent of vapor in air,		
	by volume, that will explode or ignite in the presence of		
	an ignition source		

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-₩ -	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the
	exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the
LC 50	
	exposed animal
ppm	Concentration expressed in parts of material per
	million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or
TC, TCo, LCio, & LCo	toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					

EC INFORMATION:

		*	*		×	×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful