

Page 1 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

	1. PRODUCT IDENTIFICATIO	N
1.1	.1 Product Name:	
	AMOUR STICKY BASE COAT	
1.2	.2 Chemical Name:	
	SOLVENT MIXTURE	
13	3 Synonyms:	
	NA NA	
1.4	.4 Trade Name:	
	AMOUR STICKY BASE COAT	
1.5	.5 Product Use:	
	MANICURE PROFESSIONAL USE ONLY	
1.6	.6 Manufacturer/Distributor's Name:	
	TRANS D, INC.	
1.7	.7 Manufacturer/Distributor's Address:	
	4286 JONESBORO ROAD, FOREST PARK, GA 30297	
1.8	.8 Emergency Phone:	·
	CHEMTREC 1-703-527-3887	CHEMTREC CUSTOMER NUMBER # 22590
1.9	.9 Business Phone:	
	1-404-363-2933	

2 COMPOSITION & INGREDIENT INFORMATION

			EXPOSURE LIMITS IN AIR					
			AC	GIH		OSHA		OTHER
CHEMICAL NAME(S)	CAS NO.	%	TLV ppm	STEL ppm	PEL ppm	STEL ppm	IDLH ppm	
BUTYL ACETATE	123-86-4 8.4	< 30	150	200	150	200	1700	150TWA
ETHYL ACETATE	141-78-6 86	< 12	200	400	NA	NA	2000	400TWA
NITROCELLULOSE	9004-70-0	< 16	(10)	NE	(10)	NE	NE	
ISOPROPYL ALCOHOL	67-63-0 32	< 7.5	400	500	400	500	2000	400TWA
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	< 5	NE	NE	NE	NE	NE	
SD ALCOHOL 40B	6-4-17-5	< 30	1900	NA	1900	NA	3300	1900TWA
CI 42090 (BLUE 1)	3844-45-9	< 1	NA	NF	NA	NA	NA	
CI 60725 (VIOLET 2)	81-48-1	< 1	NA	NF	NA	NA	NA	

*Not a hazard with this product.

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format.



Page 2 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

	•	3. HAZARD	IDENTI	FICATION					
3.1	Hazard Identification: This product is classif criteria of NOHSC:1088(2004) and ADG				EROUS GO	ODS accord	ling to the clas	sificatio	n
3.2	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingest	ion:	YES	
3.3	Effects of Exposure: INGESTION: If product is swallowed, m SKIN & EYES: Mildly to moderately irrit watering. May be irritating to skin in sor INHALATION: Vapors of this product m Symptoms of overexposure can include exceeding the levels listed in Section 2 (system depression (e.g., drowsiness, dia	ating to the eyes. Syr ne sensitive individua ay be slightly irritating coughing, wheezing, Composition & Ingrec	nptoms of o ils, especial g to the nos nasal congo lient Inform	overexposure ma ly after prolonge e, throat and oth estion, and diffic	ay include re ed contact. er tissues c culty breathi	edness, itch of the respirang. Inhalati	ing, irritation a	ınd	
3.4	Symptoms of Overexposure: Symptoms of skin overexposure in some Overexposure in eyes may cause redness			le redness, itchii	ng, and irrita	ation of affe	cted areas.		
3.5	Acute Health Effects: Mild to moderate irritation to eyes and sl dizziness, headaches and nausea.	kin near affected areas	s. Additiona	ally, high concen	trations of v	/apors can	cause drowsin	ess,	
3.6	Chronic Health Effects:								
3.7	None known. Target Organs:								_
3.7	Eyes, skin & respiratory system.								
		4. FIRST	AID ME	ASURES					
4.1	First Aid:								
	INGESTION: If ingested, do not induce very patient is vomiting, continue to offer wat Poison Control Center at 1-303-623-5716 time at which the material was ingested EYES: Splashes are not likely; however, 15 minutes. Open and close eyelid(s) to SKIN: If irritation occurs and product is ceffected area with soap and water. Do not swelling persists, contact a physician im INHALATION: Remove victim to fresh air	er or milk. Never give or the nearest Poisor and the amount of the if product gets in the ensure thorough irrig on the skin, rinse thor of wear contaminated mediately.	water or man Control Control Consultance eyes, flush ation. If irrioughly with clothing un	ilk to an uncons inter or local em that was swallon with copious am tation occurs, co lukewarm water til after it has be	cious perso ergency nui wed. nounts of lul ontact a phy r, followed b een properly	n. Contact mber. Provi sewarm wat sician. y a thoroug cleaned. If	Rocky Mounta de an estimate er for at least h washing of t irritation, redr	in of the he less or	
4.2	Medical Conditions Aggravated by Exposure: None known.				HEALT	Н		1	
	None known.				FLAMN	IABILIT	Υ	3	
					REACT	IVITY		0	
							QUIPMEN ⁻	-	
									_
ı		5. FIREFIGI		TEACHDEC			, l		_ _
5.1	Flashpoint & Method:	J. FIREFIGI	TINGN	ILASURES	1				_
J. I	ι ιαστιροπτι α ινιστίτου.								

-4°C (24°F) TCC 5.2 Autoignition Temperature: ND 5.3 Flammability Limits: Lower Explosive Limit (LEL): Upper Explosive Limit (UEL): 5.4 Fire & Explosion Hazards: RED = FLAMMABILITY WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. BLUE = HEALTH Keep container closed. Vapors are heavier than air. YELLOW = REACTIVITY WHITE = SPECIAL MEASURES 5.5 Extinguishing Methods: 0 CO₂, Halon, Dry Chemical, Foam, Water 0 = NO HAZARD 1 = MINIMAL HAZARD Firefighting Procedures: 2= SLIGHT HAZARD 3 = MODERATE HAZARD When involved in a fire, this product will ignite readily and decompose to produce 4 = SEVERE HAZARD carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



Page 3 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid tocontainers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

	7. HANDLING & STORAGE INFORMATION
7.1	Work & Hygiene Practices: Avoid prolonged or repeated contact with skin. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:
	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).
7.3	Special Precautions:
	Open containers slowly on a stable surface. Keep container tigtly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

	8. EXPOSURE CONTROLS & PERSONAL PROTECTION
8.1	Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.
8.2	Respiratory Protection: No special respiratory protection is required under normal conditions of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.
8.3	Eye Protection: Avoid eye contact. None required under normal conditions of use. However, may cause irritation in some sensitive individuals. When handling large quantities (e.g., = 1 gallon), safety glasses with side shields should be used.
8.4	Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥1 gallon), wear rubber or plastic impervious gloves.
8.5	Body Protection: No apron required when handling small quantities. When handling large quantities (e.g., = 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Density:	0.83 (H ₂ O = 1)
9.2	Boiling Point:	171 - 228°F (77.2 - 108.9 °C) calculated
9.3	Melting Point:	NA
9.4	Evaporation Rate:	>1 (n-Butyl Acetate = 1)
9.5	Vapor Pressure:	Heavier than air.
9.6	Molecular Weight:	NA
9.7	Appearance & Color:	Transparent to pale blue/green viscous liquid with an sweet ester-like odor.
9.8	Odor Threshold:	ND
9.9	Solubility:	Moderately soluble in water.
9.10	рН	NA
9.11	Viscosity:	NA
9.12	Other Information:	VOC: 1.85 lb/gl



Page 4 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

	10. STABILITY & REACTIVITY		
10.1	Stability:	Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).	
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO2).	
10.3	Hazardous Polymerization:	May occur, if exposed to extremely high temperatures.	
10.4	Conditions to Avoid:	This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).	
10.5	Incompatible Substances:	Exposure to or contact with extreme temperatures, strong light sources or incompatible materials.	

		11. TOXICOLOGICAL INFORMATION
11.1	Toxicity Data:	This product has not been tested on animals to ob tain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity:	See Section 3.3
11.3	Chronic Toxicity:	See Section 3.6
11.4	Suspected Carcinogen:	Yes. This product contains Isopropyl Alcohol, which is classified as a Group 3 carcinogen (not classifiable as a human carcinogen) by the IARC.
11.5	Reproductive Toxicity:	None
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to poduce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.
11.6	Irritancy of Product:	See Section 3.3
11.7	Biological Exposure Indices:	NE
11.8	Physician Recommendations:	Treat symptomatically.

		12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows:
		Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H2O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
		Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log Kow = 0.05-0.14.
		Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.



Page 5 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

	13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal: Dispose of in accordance with all Federal, state, and local regulations.
13.2	Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

	14. TRANSPORTATION	INFORMATIO	N	
	basic description (proper shipping name, hazard class & division, ID Number, pational descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and		n for each mode of transp	ortation.
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (< 1.0 L). 1263, PAINT, 3, II (> 1.0 L).			
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (< 0.5 L). 1263, PAINT, 3, II (> 0.5 L).	CONSUMER COMMODITY	V	Anna Bir
14.3	IMDG (OCN): PAINT, 3, UN1263, II, LTD QTY	ORM-D		3 Clours
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTIT É LIMITÉE" or "LTD QTY"			PAINT UN1263

	15. REGULATORY INFORMATION			
15.1	SARA Reporting Requirements:			
	SARA 304 (40 CFR Table 302.4) - Butyl Acetate, Ethyl Acetate			
15.2	SARA Threshold Planning Quantity:			
	There are no specific Threshold Planning Quantities for the components of this product.			
15.3	TSCA Inventory Status:			
	The components of this product are listed on the TSCA Inventory.			
15.4	CERCLA Reportable Quantity (RQ):			
	Butyl Acetate = 5000 lbs (2270 kgs); Toluene = 1000 lbs (454 kgs); Dibutyl Phthalate = 10 lbs (4.54 kgs)			
15.5	5 Other Federal Requirements:			
	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cos	metics).		
15.6	Other Canadian Regulations:			
	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.			
15.7	State Regulatory Information: Butyl Acetate, Ethyl Acetate, and Isopropyl Alcohol are covered under specific state criteria.			

16. OTHER INFORMATION			
16.1	Other Information:		
	WARNING: Flammable! Keep away from heat.		
16.2	Terms & Definitions:		
	See page 6 of this MSDS.		
16.3	Disclaimer:		
	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Trans D, Inc. knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein related only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		



Page 6 of 6

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS AMOUR STICKY BASE COAT Revision Date: 4-08-2013

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists				
TLV	TLV Threshold Limit Value				
OSHA U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person					
	whose heart has stopped receives manual chest					
	compressions and breathing to circulate blood and provide					
	oxygen to the body.					


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard		
1 Slight Hazard			
2 Moderate Hazard			
3	Severe Hazard		
4	Extreme Hazard		



PERSONAL PROTECTION RATINGS:







OTHER STANDARD ABBREVIATIONS:

NA	Not Available				
NR	No Results				
NE	NE Not Established				
ND Not Determined					
ML	Maximum Limit				
SCBA Self-Contained Breathing Apparatus					


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition		
remperatore	in all will no other source of ignillion		
LEL Lower Explosive Limit - lowest percent of vapo			
	volume, that will explode or ignite in the presence of		
	an ignition source		
UEL	Upper Explosive Limit - highest percent of vapor in air,		
	by volume, that will explode or ignite in the presence of		
	an ignition source		

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
-W-	Use No Water		
OX	Oxidizer		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD _{Io} Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom			
TD _{Io} , LD _{Io} , & LD _o or TC, TC _o , LC _{Io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects			
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TLm	Median threshold limit			
log Kow or log Koc	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	TC Transport Canada				
EPA U.S. Environmental Protection Agency					
DSL Canadian Domestic Substance List					
NDSL Canadian Non-Domestic Substance List					
PSL Canadian Priority Substances List					
TSCA U.S. Toxic Substance Control Act					
EU European Union (European Union Directive 67/548/EEC)					
CPR	Canadian Controlled Product Regulations				

EC INFORMATION:

T.		*	*		X	×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful