

MATERIAL SAFETY DATA SHEETS

Page 1 of 6

## SECTION I: SUBSTANCE IDENTIFICATION AND COMPANY INFORMATION

#### MANUFACTURER'S NAME: ENTITY BEAUTY INC.

ADDRESS: 440 W. ONTARIO STREET CHICAGO, IL 60654 USA

PRODUCT TYPE: UV NAIL GELS

PRODUCT USE: NAIL GEL

USA/CANADA EMERGENCY TELEPHONE: 1.800.535.5053 INTERNATIONAL EMERGENCY TELEPHONE: 1.352.323.3500 INFORMATION CONTACT: INFOTRAC

ENTITY'S FORMULA NUMBER: CONFIDENTIAL PRODUCT CODE: 4020409-4020412, 4022342-4022345 FAMILY: UV GELS TRADE NAME: ENTITY ONE GELS CLEAR, PINK, WHITE, NATURAL WHITE ISSUED: JULY 7, 2008

## SECTION II: COMPOSITION AND INGREDIENT INFORMATION

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH	Carcinogen	%
				TWA/STEL	TWA/STEL	IARC/NTP/OSHA	
Polyurethane Acrylate	Exempt	N/E	Di-Hema	N/E	N/E	Not Listed	80-90
Oligomer	-		Trimethylhexyl Dicarbamate*				
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	Hydroxypropyl methacrylate	N/E	N/E	Not Listed	1-10
Hydroxycyclohexyl phenyl	947-19-3	213-426-9	Hydroxycyclohexyl	N/E	N/E	Not Listed	0-1
ketone			phenyl ketone				
Silicon Dioxide*	60676-86-0	262-373-8	Silica	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
May Contain the following:	Please see Se	ection 16 for ad	ditional compounds				
N/E - None Established N/R - Not Reviewed	N/DA - No D N/A - Not	ata Available Applicable	* See section 16				

Hazard Symbols: Xi Risk Phrases: R22, R36/38, R43 Safety Phrases: S18, S24/25, S36/37, S38

# SECTION III: HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This information may be based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause eye irritation.

## Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	No specific information is available for this product. Although, this product opposes only slight irriation concern with all routes of entry.
Еуе	No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.
Skin	No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.
Ingestion	No specific information available. Contains materials that may be practically nontoxic.
Inhalation	No specific information available. Low volatility makes vapor inhalation unlikely.
Sub-Chronic Effects	No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.
NOTE: Pafer to Section 11	Travical agrical Information for Datails

NOTE: Refer to Section 11, Toxicological Information for Details

ENTITY'



Spill or Release

Procedures

MATERIAL SAFETY DATA SHEETS

## SECTION IV: FIRST AID MEASURES

First Aid for Eye	Flush with plenty of water for 15 minutes and retract eyelids eyelids often. Seek medical attention immediately.
First Aid for Skin	Remove contaminated clothing and wash contact area with soap and water for 15 minutes.
First Aid for Inhalation	In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.
First Aid for Ingestion	If appreciable quantities are swallowed, seek medical attention.

# SECTION V: FIRE FIGHTING METHODS

Flash Point (°F/°C) > 212°F/100°C Setaflash		Flammable Limit (vol%) No Data	Auto-ignition Temperature (vol%) No Data				
Method: Extinguishing Media:		oxide or dry chemical for small fires; aqueous					
Fire Fighting Instructions:		Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.					
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to fires since frothing can occur.						

# SECTION VI: ACCIDENTAL RELEASE MEASURES

Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

# SECTION VII: HANDLING AND STORAGE

Handling	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods ( including shoes ). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.
	Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheatings of product, this will also diminishing the quality of the product.
Storage	Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.
Explosion Hazard	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

ENTITY'



MATERIAL SAFETY DATA SHEETS Page 3 of 6

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

#### **Personal Protective Equipment**

i ci sonai i i otective Equi	
General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Wear chemical splash goggles.
Skin Protection	Wear impervious gloves (Neoprene).
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be
	permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure
	limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the
	respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN
	149.

# SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Clear to slight			& Odor Threshol eteristic acrylate od	1 1		Specific Gravity         Visco           (H2O=1): 1.15         N/E					
Boiling Point/ Freezing Point	-	Decomposition Temperature Coefficient Log Po/w		Vapo Pressu		Vapor Density	-	oration ate	Ignitio	on	Solubility In Water (20°C)
N/A	N/A		N/A	(mm Hg) C : < 0.		No Data	No	Data	No Da	nta	Insoluble
Flash Point         (°F/°C)           > 212°F/100°C Setaflash         >			(vol	ble Limit 1%) Data	Auto-ignition Temperature (vol%) No Data			rature			

## SECTION X: STABILITY AND REACTIVITY

Stability

Normally Stable

#### Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

#### Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

#### Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

#### **Conditions to Avoid:**

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

## SECTION XI: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye	
No information available	No information available	No information available	No information available	No information	
				available	
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers.					
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.					

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA



# SECTION XII: ECOLOGICAL INFORMATION

<b>Ecotoxicological Information</b>	n			
Acute Toxicity	Acute Toxicity	Acute Toxicity	Bioconcentration	Toxicity to Sewage Bacteria
to Fish	to Invertebrates	to Algae		
N/DA	N/DA	N/DA	N/DA	N/DA
<b>Chemical Fate Information</b>				
Biodegradability	N/DA			
Chemical Oxygen Demand	N/DA			
To the best of our knowledge, the	e ecotoxocological and chem	ical fate properties have	not been thoroughly invest	stigated.

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigate

Do not allow to enter drinking water supplies, wastewater, or soil

# SECTION XIII: DISPOSABLE CONSIDERATION

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations. Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

# SECTION XIV: TRANSPORTATION INFORMATION

DOT (49 CFR 172)		
Proper Shipping Name:	Non-Regulated Material	
Identification Number:	N/A	
Marine Pollutant:	No	
Special Provisions:	N/A	
Emergency Response Guidebook (ERG) #:	N/A	
IATA (DGR):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Packaging Instructions:		
Emergency Response Guidance (ICAO)#:		
IMO (IMDG):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Special Provisions & Stowage/Segregation:	None	
Emergency Schedule (EmS)#:		
Other Information:	Flash point > 100°C	

# SECTION XV: REGULATORY INFORMATION

#### **US Federal Regulations**

es reactai Regulations	
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S.
	Clean Air Act:
	• NONE
	This product contains no ODS's
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.



# MATERIAL SAFETY DATA SHEETS Page 5 of 6

Occupational Safety and Health	This product is considered to be a hazardous chemical under the OSHA Hazard
Act	Communication Standard. Its hazards are:
	• Immediate (acute) health hazard
	• Delayed (chronic) health hazard
	Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	<ul> <li>This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.</li> <li>NONE</li> </ul>
SARA Title III: Section 302 (RQ)	• This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard
	and is regulated under Section 311-312 (40 CFR 370). Its hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of
	Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part
	372.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with
	TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

# **State Regulations**

State Regulations	
CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9.
NJ Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9.
PA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9.
FL Right-to-Know Law:	Silicon Dioxide, CAS#7631-86-9.
MN Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Silicone Dioxide, CAS#7631-86-9.


#### **International Regulations**

Inter national Regulations	
CDSL: Canadian Inventory	Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B
(on Canadian Transitional List)	Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da
	Titanium dioxide CAS # 13463-67-7 is on the DSL list. WHMIS = $n/da$
	Silicon Dioxide, CAS#7631-86-9 is on the DSL list. WHMIS = $n/da$
EINECS: European Inventory:	HAZARD SYMBOLS: Xi: Irritant
	• RISK PHRASES: <b>R22:</b> Harmful if swallowed, <b>R36/38:</b> Irritating to eyes and skin <b>R43:</b> May cause sensitization by skin contact.
	• SAFETY PHRASES: <b>S18</b> : Handle and open container with care, <b>S24/25</b> : avoid contact with skin and eyes, <b>S36/37</b> : Wear suitable protective clothing and gloves, <b>S38</b> : in case of insufficient ventilation, wear suitable respiratory equipment.



Page 6 of 6

## SECTION XVI: OTHER INFORMATION



The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.