

Manufacturer's Safety Data Sheet

SECTION I: PREPARATION IDENTIFICATION AND COMPANY INFORMATION

MANUFACTURER'S NAME: ENTITY BEAUTY INC.

EMERGENCY TELEPHONE No: 1 800 535 5053

INFORMATION CONTACT: INFOTRAC

ADDRESS: 4700 MILLENIA BOULEVARD SUITE 150
ORLANDO, FLORIDA 32839

ENTITY'S FORMULA NUMBER: CONFIDENTIAL

PRODUCT CODE: CII 106

FAMILY: NITROCELLULOSE LACQUER

PRODUCT TYPE: NAIL LIQUID

TRADE NAME: NATURAL WHITE NAIL ENAMEL

PRODUCT USE: NAIL COATING

ISSUED: 22 JUNE 2007 (REVISION 1)

SECTION II: COMPOSITION AND INGREDIENT INFORMATION

CAS Number	EINECS#	U. S. INCI	EU INCI	R Phrase	S Phrase
141-78-6	205-500-4	Ethyl acetate	Ethyl acetate	11,36,66,67	2,16,26,33
123-86-4	204-658-1	Butyl acetate	Butyl acetate	10,66,67	2,25
67-63-0	200-661-7	Isopropyl alcohol	Isopropyl alcohol	11,36,37	2,7,16,24/25,26
9004-70-0	None	Nitrocellulose	Nitrocellulose		2,35
N/A	None	Polyester resin	None		
115-86-6	204-112-2	Triphenylphosphate	Triphenylphosphate		
6846-50-0	229-934-9	Trimethyl pentanyl diisobutyrate	None		

Hazard Symbols: Xi F

Safety Phrases: S2, S7, S16, S24/25, S26, S33, 35 Risk Phrases: R11, R36, R66, R67

Chemical Identity	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Ethyl acetate	400 ppm	400 ppm	Not listed	27-34
Butyl acetate	150 ppm	150 ppm	Not listed	24-29
Isopropyl alcohol	400 ppm	400 ppm	Not listed	15-20
Nitrocellulose	400 ppm	N/E	Not listed	9-11
Polyester resin	N/E	N/E	Not listed	6-7
Triphenylphosphate	N/E	N/E	Not listed	3-4
Trimethyl pentanyl diisobutyrate	N/E	N/E	Not listed	3-4

N/E =None
Established

SECTION III: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- Flammable liquid and vapour!
- May cause eye irritation.
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.
- Relevant risk phrases - **R11: highly flammable**, **R36: Irritating to eyes**, **R37: Irritating to respiratory system**, **R67: Vapours may cause drowsiness and dizziness**.
- Please read entire MSDS for additional information.



Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry:	Inhalation, skin, eyes, ingestion
Eye:	Vapour or liquid exposure may cause irritation of eyes. Symptoms of exposure may include stinging, tearing and/or redness.
Skin:	Liquid concentration may cause moderate skin irritation. Repeated or prolonged contact may cause skin dryness or cracking. Other symptoms may include burning, dermatitis or dermal damage.
Ingestion:	Causes a burning sensation of the mouth, throat and respiratory tract, nausea, gastrointestinal irritation and abdominal pain.
Inhalation:	High vapour concentrations may irritate the respiratory system. Prolonged exposure can lead to drowsiness and dizziness, narcosis, fatigue and loss of coordination.
Chronic Health Effects	Unlikely to present a cancer hazard in man.
NOTE: Refer to Section 11, Toxicological Information for Details	

SECTION IV: FIRST AID MEASURES

First Aid for Eye:	Flush with water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.
First Aid for Skin:	Wash thoroughly with soap and water. Remove contaminated clothing and wash before re-use. Seek medical attention if discomfort persists.
First Aid for Inhalation:	Remove to fresh air. Seek medical attention immediately. If having breathing difficulty, give oxygen.
First Aid for Ingestion:	Seek medical advice immediately. Remove to fresh air. Rinse out mouth with water or induce vomiting only if directed by a physician. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to avoid aspiration into lungs.

SECTION V: FIRE FIGHTING MEASURES

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
Tag Closed Cup: 24°F/-4°C	LEL: 1% ; UEL : 13%	392.8°C

Method:	UN number: UN1263
Extinguishing Media:	Foam, carbon dioxide, dry chemical
Fire Fighting Instructions:	Wear self-contained breathing apparatus and full protective clothing. DO NOT USE WATER SINCE PRODUCT WILL FLOAT ON TOP OF THE WATER AND MAY SPREAD THE FIRE. Water spray or running water may be used to keep fire-exposed containers cool.
Unusual Hazards:	Flammable. Vapours may travel to source of ignition and flash back. Avoid ignition sources or excessive temperatures. Closed containers may rupture explosively.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Spill or Release Procedures:	Eliminate all sources of heat and ignition. Use suitable protective clothing. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer - although product is not labelled as dangerous to the environment EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapours, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. .
------------------------------	--

SECTION VII: HANDLING AND STORAGE

Handling:	Keep away from heat, sparks and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Wash thoroughly after handling.
Storage:	Store in a cool, dry area. Keep container closed when not in use. Store at ambient temperatures out of direct sunlight. Store in a well ventilated place. Store in accordance with National Fire Protection Association recommendations.
Explosion Hazard:	Avoid ignition sources or excessive temperatures. Closed containers may rupture explosively.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls:	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
Personal Protective Equipment	
General:	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) or UK CoSHH regulations (or other appropriate EU legislation) be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole bodysuit. Nitrile rubber is better than PVC. For professional use in beauty salons, the use of a fan is recommended to provide fresh air supplies to operator.
Eye/ Face Protection:	Always check suitability of equipment with the supplier. Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.
Skin Protection:	Use impermeable clothing to prevent any contact with this product, such as gloves, apron, boots, or a whole body suit. Neoprene and nitrile rubber is better than PVC.
Respiratory	A NIOSH/MSHA approved air purifying respirator with an organic vapour

Protection: cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-face piece airline respirator in the positive pressure mode with emergency escape provisions.
Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard 149.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odour & Odour Threshold	pH	Specific Gravity	Viscosity	% Volatile -	Solubility In Water (20°C)
Opaque liquid various colours	Acetate odour	N/A	(H ₂ O=1): 0.85-0.97	N/A	70-80% by weight	negligible
Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient	Vapour Pressure:	Vapour Density	Evaporation Rate	Ignition
77- 130°C N/DA	N/DA	N/A	mm Hg: 29 @ 20°C	(Air=1): 3.04	Isopropyl alcohol = 1 : <1	N/A
Flash Point (°F/°C)		Flammable Limit (vol%)		Auto-ignition Temperature (vol%)		
Tag Closed Cup: 24°F/ -4°C		LEL : 1% ; UEL : 13%		N/A		

SECTION X: STABILITY AND REACTIVITY

Stability: Chemically stable under normal conditions	Incompatibility (Materials to Avoid): Reducing and oxidizing agents, acids, alkalis, metals, amines
Hazardous Decomposition Products: Oxides of nitrogen, carbon and phosphorous	Hazardous Polymerization: Will not occur
Conditions to Avoid: Temperatures above 35°C, oxidizing or reducing agents, avoid ignition sources.	

SECTION XI: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
Oral LD50 (rat): Ethyl acetate = 11300 mg/kg; butyl acetate = 11400 mg/kg; isopropyl alcohol = 5840 mg/kg	No data	Inhalation LC50 (rat): Ethyl acetate = 1600 ppm; butyl acetate = 2000 ppm; isopropyl alcohol = 16000 ppm	No data	No data
Sensitisation	Mutagenicity	Sub-chronic Toxicity		
No data	No data	No data Possible target organ is the nervous system		

SECTION XII: ECOLOGICAL INFORMATION

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No data	No data	No data	No data	No data

Chemical Fate Information

Biodegradability	No data
Chemical Oxygen Demand	No data

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

SECTION XIII: DISPOSAL CONSIDERATIONS

Dispose of diking and absorbent materials in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to an approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements

SECTION XIV: TRANSPORT INFORMATION

DOT (49 CFR 172)	
Proper Shipping Name:	Paint (ethyl acetate, butyl acetate, isopropyl alcohol), 3, PGIII
Identification Number:	UN1263
Marine Pollutant:	No
Special Provisions:	T8, T31
Emergency Response Guidebook (ERG) #:	128
IATA (DGR):	
Proper Shipping Name:	Paint (ethyl acetate, butyl acetate, isopropyl alcohol), 3, PGII
Class or Division:	3
UN or ID Number:	ID8000
Packaging Instructions:	PGII
Emergency Response Guidance (ICAO)#:	305, 307
IMO (IMDG):	
Proper Shipping Name:	Paint (ethyl acetate, butyl acetate, isopropyl alcohol), 3, PGIII
Class or Division:	3
UN or ID Number:	UN1263
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	FE, SE
Other Information:	Flash point = -4°C

SECTION XV: REGULATORY INFORMATION


International Regulations

CDSL: Canadian Inventory	Ethyl acetate DSL regulatory status: Included, WHMIS: B2:
--------------------------	---

(on Canadian Transitional List)	flammable liquid, D-2B:Toxic Butyl acetate DSL regulatory status: Included, WHMIS: B2: flammable liquid, D-2B:Toxic Isopropyl alcohol DSL regulatory status: Included, WHMIS: B2: flammable liquid, D-2B:Toxic Nitrocellulose DSL regulatory status: Included, WHMIS: not known Polyester resin DSL regulatory status: not known, WHMIS: not known Triphenyl phosphate DSL regulatory status: Included, WHMIS: not known Trimethyl pentanyl diisobutyrate DSL regulatory status: Included, WHMIS: not known
EINECS: European Inventory:  	# 010 NATURAL WHITE HAZARD SYMBOLS: Xi, F: Irritant, Highly Flammable - RISK PHRASES: R10: <i>flammable,</i> R11: <i>highly flammable,</i> R36: <i>Irritating to eye.</i> R37: <i>Irritating to respiratory system</i> R66: <i>repeated exposure may cause skin dryness or cracking,</i> R67: <i>vapours may cause drowsiness and dizziness</i> SAFETY PHRASES: S2: <i>keep container in a well ventilated place,</i> S7: <i>keep container tightly closed</i> S16: <i>keep away from sources of ignition- no smoking,</i> S24/25: <i>avoid contact with skin and eyes,</i> S26: <i>in case of contact with eyes, rinse immediately with plenty of water and seek medical advice</i> S33: <i>take precautionary measures against static discharges,</i> S35: <i>this material and its container must be disposed of in a safe way</i>

SECTION XVI: OTHER INFORMATION

Hazard Rating System (Pictograms)



The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.