Page 1 of 7

MSDS-018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

			1. PRC	DUCT IDE	NTIFIC	ATIC)N							
1.1	Product Name: BOND-AID®													
1.2	Chemical Name: SOLVENT MIXTURE													
1.3	Synonyms:													
1.4	NA Trade Names:													
	BB010, BB020													
1.5	Product Use: COSMETIC USE ONLY													
1.6	Manufacturer's Name:													
1.7	OPI PRODUCTS, INC. Manufacturer's Address:													
1.8	13034 SATICOY STREET, I Emergency Phone:	NO. HOLLYWOO	D, CA 91605 U	SA										
1.0	CHEMTREC: +1 (703	3) 527-3887 /	+1 (800) 42	4-9300										
1.9	Business Phone:	-												
	+1 (818) 759-2400 / +1 (800)-341-9999												
			2. HA	ZARD IDE	NTIFIC	ATIO	N							
2.1	Hazard Identification:							_						
	This product is classified NOHSC:1088 (2004) and			ANCE and as mmable liquid		ROUS	GOOD	S acc	ording	to th	ne cla	ssificat	ion cr	iteria of
2.2	Routes of Entry:		Inhalation:	YES	Ak	osorptic	on:	Y	ΈS	Ing	jestion	:	Y	ES
2.3	Effects of Exposure:	t is swallowed,												
	SKIN & EYES:Mildly to moderately irritating to the eyes.Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.INHALATION:Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system.Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing.Inhalation of vapors exceeding the levels listed in Section 2 (Composition & Ingredient Information) can cause central nervous system						act. mptoms vapors							
2.4	depression (e.g., drowsiness, dizziness, headaches, nausea). Symptoms of Overexposure: Symptoms of skin overexposure in some sensitive individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.						l areas.							
2.5	Acute Health Effects: Mild to moderate irritat dizziness, headaches a		d skin near aff	ected areas.	Addition	ally, hi	gh co	ncentr	ations	of vap	oors co	an cau	se dro	wsiness,
2.6	Chronic Health Effects:													
2.7	None known. Target Organs:													
2.7	Eyes, skin & respiratory	system.												
		3. CC	MPOSITIC	ON & INGR		T INF	ORA	ΛΑΤΙ	ON					
								EXPC	SURE L		N AIR			•
						AC			NOHSC	:		OSHA		OTHER
						pp	om	ES-	ppm ES-	ES-		ppm		
	CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK		STEL	IDLH	
ETHYI		141-78-6	AH5425000 ZC0110000	205-500-4 231-791-2	≤ 100.0	400	NE	720 NE	1440 NE	NF	400	NE	2000	400 TWA
		7732-18-5	BQ9625000	231-791-2	< 1.0 ≤ 1.0	NE 25	NE NA	NF NF	NF NF	NF NF	NE 25	NE NA	NE NA	
		1000-21-0	5.47023000	215-04/-0	- 1.0	23	NA				23	An	An	I
	= Not Available; ND = Not E: all WHMIS required info				0								rms Use	ed

$0 \cdot \mathbf{P} \cdot \mathbf{I}$	
---------------------------------------	--

Page 2 of 7

MSDS-018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

			4. FIRST AID MEAS	URES				
4.1	First Aid: INGESTION:	patient is vomiting, cont nearest Poison Control C	e vomiting. If product has been s tinue to offer water or milk. Never Center or local emergency number It of the substance that was swallow	give water o r. Provide an	r milk to an	unconsciou	s person. Co	ontact the
	EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If irritation occurs, contact a physician.						or at least	
	SKIN:	If irritation occurs and putter the effected area with so	roduct is on the skin, rinse thoroug oap and water. Do not wear conto lling persists, contact a physician ir	hly with lukew minated clot	varm water, f	followed by	a thorough v	-
	INHALATION:		ir at once. If breathing stops, perfo	rm artificial re	espiration. Se	eek immedi	ate medical (attention.
4.2	Medical Condition	is Aggravated by Exposure:			HEALTH	ł		1
	None known.				FLAMN	ABILITY		3
					REACT	Ινιτγ		0
					PROTE	CTIVE EG	UIPMEN	ΓΑ
					EYES			
			5. FIREFIGHTING ME	ASURES				
5.1	Flashpoint & Metho -4°C (24°F) TC							
5.2	Autoignition Temp							
	860°F				-			1
5.3	Flammability Limits		Lower Explosive Limit (LEL):	2.2%	Upper Exp	plosive Limit	(UEL):	11. 4 %
5.4	Fire & Explosion Ha		om heat, lit cigarettes, sparks & or	oen flame Ke	een contain	er closed		
	When heated	above the flashpoint, er	mits flammable vapors which, wh mable at temperatures below the f	en mixed wit	•			
5.5	Extinguishing Meth		•	•				
	CO ₂ , Halon, Dry Chemical, Foam							
5.6	Firefighting Procedures:							
		ication Number: 33						<u> </u>
	This product i decompose t	s a Class IB flammable o produce carbon oxide	liquid. When involved in a fire, t s. Vapors of this product are he taking or open container.	•	-	-		/
	equipment. l		tection. Structural firefighters mu to reduce or direct vapors. Wate ct.					
					F C			
6.1	Spills:	6	. ACCIDENTAL RELEASE	MEASUR	E3			
0.1		ng any spill or leak, individ	duals involved in spill cleanup mus	l wear approp	oriate Person	al Protective	e Equipment.	
	doors and wir closed contai	ndows) and secure all sou ner(s) for disposal. Dispos	ppropriate personal protective equ urces of ignition. Remove spilled r se of properly in accordance with of warm water and soap. Remov	naterial with a local, state ar	absorbent m nd federal re	aterial and gulations. N	place into a _l Vash all affec	opropriate ted areas
	non-sparking separate cont	tools for recovery and a ainers for proper disposal	protected individuals. Dike and co cleanup. Transfer liquid to conta I. Remove contaminated clothing nunicipal sewers and open bodies	iners for reco promptly and	very or disp	oosal and s	olid diking n	naterial to

Page 3 of 7

MSDS-018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap & water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. 7.3 Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 81 Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 82 **Respiratory Protection** No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.3 Eve Protection Avoid eye contact. None required under normal conditions of use. However, may cause irritation in some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon), safety glasses with side shields should be used. 84 Hand Protection None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves. 8.5 Body Protection No apron required when handling small quantities. When handling large quantities (e.g., \geq 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES Density: 9.1 0.902 92 Boiling Point: 172°F 9.3 Melting Point NA 9.4 Evaporation Rate: NA 95 Vapor Pressure NA 9.6 Molecular Weight: NA 9.7 Appearance & Color: Clear liquid with characteristic fragrant, fruity odor. Odor Threshold 9.8 ND 99 Solubility: Miscible with alcohol, ether, glycerin, volatile oils, water, most organic solvents. 9.10 рΗ NA 9.11 Viscosity Non-viscous. 9.12 Other Information: NA

$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$
--

Page 4 of 7

U	J.L.I					MSDS-018
Prep	ared to OSHA. ACC	C, ANSI, NOHSC, WHMIS & 20	001/58 FC Standards	MSDS Revision: 2.0	MSDS Revision D	ate: 08/01/2008
		1	IO. STABILITY &	REACTIVITY		
10.1	Stability:					
10.1		vient conditions when stored	l properly (see Section	n 7. Storage and Handling	a).	
10.2	Hazardous Decomposit				57.	
	If exposed to ext	remely high temperatures,	the products of therm	al decomposition may i	include irritating vapor	s and carbon oxide
	gases (e.g., NH ₃ , (CO, CO ₂).				
10.3	Hazardous Polymerizatio		_			
		osed to extremely high tem	peratures.			
10.4	Conditions to Avoid: None reported.					
10.5	Incompatible Substanc	es:				
	•	ompatible with strong oxidi	izers (e.a., peroxides,	superoxides), strong aci	ds (e.a., hvdrochloric c	or muriatic acids), or
		, lye, potassium hydroxide)		.		, , , , , , , , , , , , , , , , , , ,
		11. T	OXICOLOGICA	AL INFORMATION		
11.1	Toxicity Data:					
	This product has	not been tested on anima	ls to obtain toxicolog	jical data. There are to	xicology data for the	components of this
		e found in the scientific liter	ature. These data hav	ve not been presented in	this document.	
11.2	Acute Toxicity:					
11.0	See Section 2.5 Chronic Toxicity:					
11.3	See Section 2.6					
11.4	Suspected Carcinogen					
	No					
11.5	Reproductive Toxicity:					
	This product is not	reported to cause reprodu	ctive toxicity in huma	ns.		
	Mutagenicity:					
	Embryotoxicity:	reported to produce mutag	genic effects in humai	ns.		
	, ,	reported to produce embry	votoxic effects in hum	ans		
	Teratogenicity:					
	This product is not	reported to cause teratoge	enic effects in humans	•		
	Reproductive Toxicity:					
		reported to cause reprodu	ctive effects in humar	IS.		
11.6	Irritancy of Product:					
11 7	See Section 2.3	0.001				
11.7	Biological Exposure Indi NE	ces.				
11.8	Physician Recommenda	ations:				
	Treat symptomatic	cally.				
		12.	ECOLOGICAL	INFORMATION		
12.1	Environmental Stability:					
		of this product will slowly a components of this product		to a variety of organic o	compounds. Specific	environmental data
	significant. This compound's half-	c = 0.73. Water solubility: 6 compound can be remo life in water is 6.1 hours.				
12.2	Effects on Plants & Anim					
10.0		ific data available for this p	roduct.			
12.3	Effects on Aquatic Life:	ecific data available for th	his product however	very large releases of	this product may be	harmful or fatal to
	overexposed aqu			tery large releases of	inis prodoci indy be	

	·P·I MATERIAL SA	FETY DATA SHEET	Page 5 of 7
Ŭ	ared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standa	rds MSDS Revision: 2.0 MSDS Rev	/ision Date: 08/01/2008
iep	area to OSHA, ACC, ANSI, NOHSC, WHIMIS & 2001/30 EC Standa		NSION Date. 00/01/2000
		CONSIDERATIONS	
3.1	Waste Disposal: Waste disposal must be in accordance with appropriate Feder	al, state, and local regulations.	
3.2	Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic – ignitable)		
		TION INFORMATION	
	basic description (proper shipping name, hazard class & division tional descriptive information may be required by 49 CFR, IATA/I		ich mode of transportation
4.1			
	CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1173, ETHYL ACETATE, 3, II (> 1.0 L)		
4.2	IATA (AIR):		
	CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1173, ETHYL ACETATE, 3, II (> 0.5 L)		
4.3	IMDG (OCN):		
	UN1173, ETHYL ACETATE, 3, II, LTD QTY (≤ 1.0 L) UN1173, ETHYL ACETATE, 3, II (> 1.0 L)		CONSUMER COMMODITY
4.4	TDGR (Canadian GND):		ORM-D
	MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or " UN1173, ETHYL ACETATE, 3, II (> 1.0 L)	'LTD QTY" or "QUANT LTEE" (≤ 1.0 L)	OWN-D LANELINATER OWCADDA SINN
4.5	ADR/RID (EU):		
4.6	UN1173, ETHYL ACETATE, 3, II, ADR, LTD QTY (≤ 1.0 L) MEXICO (SCT):		
4.0	UN1173, ACETATO DE ETILO, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)		
4.7	ADGR (AUS): UN1173, ETHYL ACETATE, 3, II, LTD QTY (> 1.0 L)		
- 4		RY INFORMATION	
5.1	SARA Reporting Requirements: SARA 304 (40 CFR Table 302.4) – Ethyl Acetate		
5.2	SARA Threshold Planning Quantity:		
5.3	There are no specific Threshold Planning Quantities for the com ISCA Inventory Status:	ponents of this product.	
	The components of this product are listed on the TSCA Inventor	у.	
5.4	CERCLA Reportable Quantity (RQ): Ethyl Acetate – 2270 kg; 5000 lbs. Ammonium Hydroxide – 450	ka: 1000 lbs.	
5.5	Other Federal Requirements:		
5.6	This product complies with the appropriate sections of the Food Other Canadian Regulations:	d and Drug Administration's 21 CFR subchapt	ter G (Cosmetics).
0.0	This product has been classified according to the hazard criter		
	the information required by the CPR. The components of this p of the components of this product are listed on the Priorities Sub		
5.7	State Regulatory Information:		
	Ingredients in this mixture on found on the following state criteri	IQ 11515.	
	California OSHA Hazardous Substances List Delaware Air Quality Management List	Ethyl Acetate Ethyl Acetate, Ammonium Hydroxide	
	Massachusetts Hazardous Substances List	Ethyl Acetate, Ammonium Hydroxide	
	Minnesota Hazardous Substances List	Ethyl Acetate	
	New Jersey Right to Know Hazardous Substances List New York List of Hazardous Substances	Ammonium Hydroxide Ethyl Acetate, Ammonium Hydroxide	
	Pennsylvania Hazardous Substances List	Ethyl Acetate, Ammonium Hydroxidew	
	Washington Permissible Exposure Limits for Air Contaminants	Ethyl Acetate	
	Wisconsin Hazardous Substances List	Ethyl Acetate	

C	·P·I	MAT	ERIAL SAFE	TY DATA SH	EET	Page 6 of 7 MSDS-018		
Prep	ared to OSHA, AC	C, ANSI, NOHSC, WHMIS	& 2001/58 EC Standards	MSDS Revision: 2.0	MSDS Revision Da	te: 08/01/2008		
		15. RE	GULATORY INFOR	MATION - continue	d			
15.8	5.8 67/548/EEC (European Union) Requirements: The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: <u>Ethyl Acetate</u> : Flammable (F), <u>Ammonium Hydroxide</u> (Xi) Irritant. R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition – No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.							
16.1	16. OTHER INFORMATION 6.1 Other Information: Keep out of reach of children. Do not take internally. Keep away from heat and open flame.							
16.2	Terms & Definitions:			·				
16.3	Please see last page of this MSDS. 16.3 Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.							
16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Stro No. Hollywood, C +1 (818) 759-2400 +1 (818) 759-5770 http://www.opi.c	eet A 91605 USA phone Ifax	0·P·I					
16.5	Prepared by: ShipMate, Inc. PO Box 787 Sisters, OR 97759 Phone: +1 (310) 3 Fax: +1 (310) 370- e-mail: shipmate	70-3600 5700	ShipMa Dangerous O Training & C					



Page 7 of 7

MSDS-018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

DEFINITION OF TERMS

MSDS Revision Date: 08/01/2008

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienist					
TLV	Threshold Limit Value					
OSHA	U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit					
IDLH	Immediately Dangerous to Life and Health					
	Infinediately Bangeloas to Elic and fleatth					

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.

HEALTH

FLAMMABILITY

PERSONAL PROTECTION


REACTIVITY

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

PERSONAL PROTECTION RATINGS:



OTHER STANDARD ABBREVIATIONS:

NA	Not Available				
NR	No Results				
NE	Not Established				
ND	Not Determined				
ML	Maximum Limit				
SCBA	Self-Contained Breathing Apparatus				


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard Acidic				
ACD					
ALK	Alkaline				
COR	Corrosive				
-W -	Use No Water				
ОХ	Oxidizer				



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TD _{lo}	D _{lo} Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{Io} , LD _{Io} , & LD _o or	or Lowest dose (or concentration) to cause lethal or					
TC, TC _o , LC _{io} , & LC _o	toxic effects					
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	 Bioconcentration Factor 					
TLm	Median threshold limit					
log Kow or log Koc	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			

EC INFORMATION:

¶ <mark>∦</mark>		N	*	8	*	×	×
С	Е	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful