$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$ 

### MATERIAL SAFETY DATA SHEET

Page 1 of 7

MSDS-020

Prep	ared to OSHA,	ACC, ANSI, NO	OHSC, WHMIS	& 2001/58 EC S	Standards	MSDS F	Revision	: 2.1		MSDS	Revision	on Dat	e: 04/1	5/2010	)
				1 PP()[	DUCT IDE	NTIFIC	` ATIC	N							
1.1	Product Name:			I. I KOL	וטו וטט	.14111110	AIIC	<i>)</i>   1							
***	CHIP SKIP	)													
1.2	Chemical Name: SOLVENT MIXT	URE													
1.3	Synonyms:														
1.4	Trade Names: NT100, NT106														
1.5	Product Use:	E ONLY													
1.6	Manufacturer's Na														
	OPI PRODUCTS	•													
1.7	Manufacturer's Ac		HOLLYWOOD,	CA 91605 USA											
1.8	Emergency Phone														
1.9	Business Phone:	: +1 (703) 52	27-3887 / +	1 (800) 424-	9300										
	+1 (818) 759-2	400 / +1 (800)	-341-9999												
				2 ΗΔ7	ARD IDE	NTIFIC	ΔΤΙΟ	N							
2.1	Hazard Identificati	on:		<b>2</b> , 11/\(\(\(\)\)	AKD IDE		<u> </u>	11							
	•			US SUBSTANCE lammable liqui		NGEROU	s GOOI	DS acc	ording	to the	e class	sificatio	on crite	eria of	NOHSC:
2.2	Routes of Entry:			Inhalation:	YES	Ab	sorption	n:	YE	S	Inge	estion:		YE	S
2.3	Effects of Exposure INGESTION:		swallowed, ma	ay cause naus	ea, vomiting	and/or	diarrhe	a and c	entra	l nervo	us sysi	em de	pressi	on.	
	SKIN & EYES:			ating to the e											
	watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.  INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of						ptoms of								
	overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition & Ingredient Information) can cause central nervous system														
2.4	C	depression (		ss, dizziness, he											
2.4		skin overex		me sensitive		may in	clude	rednes	s, itch	ning, d	and in	ritation	of a	ffected	d areas.
0.5			cause redness	s, itching and v	watering.										
2.5	Acute Health Effect Mild to mode dizziness, hea	rate irritation		skin near affec	cted areas.	Additio	nally, hi	igh cor	ncentr	ations	of var	ors co	an cau	se dro	wsiness,
2.6	Chronic Health Effe		uuseu.												
2.7	None known.  Target Organs:														
	Eyes, skin & re	spiratory syste	em.												
			3 COM	MPOSITION	I & INCE	PEDIEN	IT INF	O P M	A TIC	)N					
			U. UU/								IMITS II	N AIR (	mg/m	3)	
							ACC	GIH	ı	NOHSC	:		OSHA		
							pp	m	ES-	ppm ES-	ES-		ppm		OTHER
	CHEMICAL NA	AME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	
ETHYL	ACETATE	•	141-86-4	AH5425000	201-550-6	≤100.0	400	NA	720	1440	NF	400	NA	2000	
AMM	ONIUM HYDROX	KIDE	1336-21-6	BQ9625000	215-647-6	≤ 1.0	25	NA	NF	NF	NF	25	NA	NA	
WATE	R (AQUA)		7732-18-5	ZC0110000	231-791-2	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
NA =	Not Available; NI	D = Not Determin	ned; NE = Not Es	stablished; NF = N	Not Found; C =	Ceiling Li	mit; See	Section	16 for <i>i</i>	Additio	nal Defi	nitions (	of Terms	Used	

NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

 $0.9 \cdot 1$ 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

### **MATERIAL SAFETY DATA SHEET**

MSDS Revision: 2.1

Page 2 of 7

MSDS-020

MSDS Revision Date: 04/15/2010

4. FIRST AID MEASURES First Aid: 4.1 INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If irritation occurs, contact a physician. SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. Do not wear contaminated clothing until after it has been properly cleaned. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention. 4.2 Medical Conditions Aggravated by Exposure: **HEALTH** 1 None known. **FLAMMABILITY** 3 REACTIVITY 0 PROTECTIVE EQUIPMENT A **EYES** 5. FIREFIGHTING MEASURES 5.1 Flashpoint & Method: -4°C (24°F) TCC 5.2 Autoignition Temperature: 800°F Flammability Limits: 5.3 2.2% Upper Explosive Limit (UEL): 11.4% Lower Explosive Limit (LEL): 5.4 WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When heated above the flashpoint, emits flammable vapors which, when mixed with air, can burn or ve explosive. Mists or sprays may be flammable at temperatures below the flashpoint. 5.5 Extinguishing Methods CO<sub>2</sub>, Halon, Dry Chemical, Foam 5.6 Firefighting Procedures HazChem Code: 3YE Hazard Identification Number: 33 This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES

6.1 Spill

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

# $O \cdot P \cdot I$

### **MATERIAL SAFETY DATA SHEET**

Page 3 of 7

MSDS-020

Dron	arad to OCLIA ACC ANGLA	OUSC WITNES & 2001/E0 EC Standards MCDC Partition 2.1 MCDC Partition Date 04/15/2010								
Prep	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS & 2001/58 EC Standards   MSDS Revision: 2.1   MSDS Revision Date: 04/15/2010								
		7. HANDLING & STORAGE INFORMATION								
7.1	. •	with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local After use, wash hands and exposed skin with soap & water. Do not eat, drink or smoke while handling								
7.2	Storage & Handling:  Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat.									
7.3		a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual erefore, empty containers should be handled with care.								
		8. EXPOSURE CONTROLS & PERSONAL PROTECTION								
8.1		quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an ishbasin is available in case of exposure to eyes.								
8.2	protection authorized per	·								
8.3	Eye Protection:  Avoid eye contact. None	required under normal conditions of use. However, may cause irritation in some sensitive individuals. ities (e.g., ≥ 1 gallon), safety glasses with side shields should be used.								
8.4	-	al conditions of use. However, may cause skin irritation in some sensitive individuals.  ities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves.								
8.5		andling small quantities.  Itities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of ge quantities of this product, wash any exposed areas thoroughly with soap and water.								
		9. PHYSICAL & CHEMICAL PROPERTIES								
9.1	Density:	0.895								
9.2	Boiling Point:	171 - 228°F								
9.3	Melting Point:	NA NA								
9.4	Evaporation Rate:	NA NA								
9.5	Vapor Pressure:	NA NA								
9.6	Molecular Weight:	NA NA								
9.7	Appearance & Color:	Clear liquid with characteristic fragrant, fruity odor.								
9.8	Odor Threshold:	ND								
9.9	Solubility:	Miscible with alcohol, ether, glycerine, volatile oils, water, most organic solvents.								
9.10	рН	NA NA								
9.11	Viscosity:	Non-viscous.								
9.12	Other Information:	NA NA								

 $O \cdot P \cdot I$ 

### **MATERIAL SAFETY DATA SHEET**

Page 4 of 7

MSDS-020

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.1 MSDS Revision Date: 04/15/2010 10. STABILITY & REACTIVITY 10.1 Stability Stable under ambient conditions when stored properly (see Section 7, Storage and Handling). 10.2 If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., NH<sub>3</sub>, CO, CO<sub>2</sub>). 10.3 Hazardous Polymerization: May occur, if exposed to extremely high temperatures. Conditions to Avoid None reported. 10.5 Incompatible Substances: This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). 11. TOXICOLOGICAL INFORMATION 11.1 Toxicity Data This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have not been presented in this document. 11 2 Acute Toxicity: See Section 2.5 11.3 Chronic Toxicity See Section 2.6 11.4 Suspected Carcinogen: Reproductive Toxicity This product is not reported to cause reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. This product is not reported to produce embryotoxic effects in humans. This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indices: ΝE 11.8 Physician Recommendations Treat symptomatically. **ECOLOGICAL INFORMATION** 12. 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate:  $K_{OC}$  = 0.72. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

 $O \cdot P \cdot I$ 

Wisconsin Hazardous Substances List

### MATERIAL SAFETY DATA SHEET

Page 5 of 7

MSDS-020

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.1 MSDS Revision Date: 04/15/2010 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND) EXCEPTED QUANTITY (49 CFR §173.4a) (≤ 30 ml) CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L) EXCEPTED QUANTITY (AIR SHIPPER § 4.1.2) (≤ 30 ml) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 0.5 L) 14.3 IMDG (OCN) EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) JMER COMMODITY UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L) ORM-D UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L) 14.4 TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L) 14.5 ADR/RID (EU) UN1263, PAINT RELATED MATERIAL, 3, II, ADR 14.6 MEXICO (SCT) **UN1263** UN1263, PRODUCTOS PARA PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L) 14.7 ADGR (Australia) UN1263, PAINT RELATED MATERIAL, 3, II, ADR 15. REGULATORY INFORMATION 15.1 SARA Reporting Requirements SARA 304 (40 CFR Table 302.4) - Ethyl Acetate 15.2 SARA Threshold Planning Quantity There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CERCLA Reportable Quantity (RQ): Ethyl Acetate - 5000 lbs; Ammonium Hydroxide - 1000 lbs 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). 15.6 Other Canadian Regulations This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid. State Regulatory Information: Ingredients in this mixture on found on the following state criteria lists: California OSHA Hazardous Substances List **Ethyl Acetate Delaware Air Quality Management List** Ethyl Acetate, Ammonium Hydroxide Massachusetts Hazardous Substances List Ethyl Acetate, Ammonium Hydroxide Minnesota Hazardous Substances List **Ethyl Acetate** New Jersey Right to Know Hazardous Substances List Ammonium Hydroxide **New York List of Hazardous Substances** Ethyl Acetate, Ammonium Hydroxide Pennsylvania Hazardous Substances List Ethyl Acetate, Ammonium Hydroxide Washington Permissible Exposure Limits for Air Contaminants **Ethyl Acetate** 

**Ethyl Acetate** 

## $0.9 \cdot 1$

### MATERIAL SAFETY DATA SHEET

Page 6 of 7

MSDS-020

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.1

MSDS Revision Date: 04/15/2010

#### 15. REGULATORY INFORMATION - continued

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC: Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system

and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.



#### 16. OTHER INFORMATION

16.1 Other Information

Keep out of reach of children. Do not take internally. Keep away from heat and open flame.

16.2 Terms & Definitions:

Please see last page of this MSDS.

16.3 Disclaimer

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $O \cdot P \cdot I$ 

16.5 Prepared by:

ShipMate, Inc. P.O. Box 787

Sisters, OR 97759-0787 USA Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700

e-mail: shipmate@shipmate.com



### **MATERIAL SAFETY DATA SHEET**

Page 7 of 7

MSDS-020

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.1

MSDS Revision Date: 04/15/2010

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No. Chemical Abstract Service Number
--

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	ACGIH American Conference on Governmental Industrial Hygienis					
TLV Threshold Limit Value						
OSHA U.S. Occupational Safety and Health Administration						
PEL Permissible Exposure Limit						
IDLH Immediately Dangerous to Life and Health						

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person							
	whose	heart	has	stopped	receives	manual	chest	
	compre	ssions a	nd bre	eathing to d	circulate bl	ood and p	rovide	
	oxyden	to the h	odv					


#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard					
1	Slight Hazard					
2	2 Moderate Hazard					
3	3 Severe Hazard					
4	Extreme Hazard					



#### PERSONAL PROTECTION RATINGS:










Respirator









or SCBA

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

Respirator

#### OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
NF	Not Found
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

#### FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion					
Temperature	<b>Temperature</b> in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by					
	volume, that will explode or ignite in the presence of					
	an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air,					
by volume, that will explode or ignite in the presenc						
	an ignition source					

#### HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
<del>-W</del> -	Use No Water		
ОХ	Oxidizer		



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD <sub>lo</sub>	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or				
TC, TC <sub>o</sub> , LC <sub>lo</sub> , & LC <sub>o</sub>	toxic effects				
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	DOT U.S. Department of Transportation						
TC	Transport Canada						
EPA	U.S. Environmental Protection Agency						
DSL	Canadian Domestic Substance List						
NDSL	Canadian Non-Domestic Substance List						
PSL	Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act						
EU	European Union (European Union Directive 67/548/EEC)						

#### EC INFORMATION:

1		*	*		×	×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful