MATERIAL SAFETY DATA SHEET

Page 1 of 7

MSDS-024

Prep	ared to OSHA, AC	CC, ANSI, NOHSC, WHMIS	& 2001/58 EC Stand	ards M	SDS Revision: 3.0	MSDS	Revision Date: 09/	/01/2008		
			1. PRODUCT	IDENTI	ICATION					
1.1	Product Name:									
	COMPETITION	ON FORMULA 300	00 E.C.T. LIQUI	D						
1.2	Chemical Name:									
	METHACRYLATE	SOLUTION								
1.3	Synonyms: NA									
1.4	Trade Names:									
	AE E02, E04, E08, E06, E07, E09									
1.5	Product Use: PROFESSIONAL USE ONLY									
1.6	PROFESSIONAL USE ONLY Manufacturer's Name:									
	OPI PRODUCTS,									
1.7	Manufacturer's Address:									
		STREET, NO. HOLLYWOOD,	, CA 91605 USA							
1.8										
1.9	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300									
1.7	Business Phone: +1 (818) 759-2400 / +1 (800)-341-9999									
	. (0.0)	(000)								
			2. HAZARD	IDENTIF	ICATION					
2.1	Hazard Identification:									
		classified as a HAZARDOU ADG Code (Australia). F		DANGER	OUS GOODS according	ng to the d	classification criter	ia of NOHSC:		
2.2	Routes of Entry:		Inhalation:	YES	Absorption:	YES	Ingestion:	YES		
2.3	Effects of Exposure:									
	INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.									
	SKIN & EYES: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g.,									
	rashes, welts, dermatitis) upon prolonged or repeated exposure.									
	INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system.									
	Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).									
2.4	Symptoms of Overex		cause ceriliai nervo	us systetiii	aepiession (e.g., drov	valitess, GI	Liness, neducine	is, Huuseuj.		
2	Symptoms of sk	kin overexposure may in								
	reaness, itcning repeated expos	and watering. The prosure.	duct can cause all	ergic skin	reactions (e.g., rasno	es, weits,	dermatitis) upon	prolonged or		
2.5	Acute Health Effects:									
	Moderate irritati headaches and	on to eyes and skin near I nausea.	affected areas. Add	ditionally, h	igh concentrations o	f vapors c	an cause drowsine	ess, dizziness,		
2.6	Chronic Health Effect	(S:								
	None known									
2.7	Target Organs:	alvedan careta								
	Eyes, skin & resp	maiory system.								
NA -	- Not Available: M	ID = Not Determined; NE :	- Not Established: C	- Ceiling Li	mit: Saa Saction 14 fo	r Addition	al Definitions of To	rms Used		
111/7 =	- rvot Avallable, N	D - NOLDCIGITIIICA, NE	- MOLESIADIBLICA, C :	- ociiii iu Li	THE SEC SECTION TO 10			TITLE CONTRACT		

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

MATERIAL SAFETY DATA SHEET

Page 2 of 7

MSDS-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 3.0 MSDS Revision Date: 09/01/2008 3. COMPOSITION & INGREDIENT INFORMATION - continued EXPOSURE LIMITS IN AIR (mg/m³) ACGIH **NOHSC OSHA** OTHER ppm ppm ppm ES-ES-ES-CHEMICAL NAME(S) CAS No. RTECS No. **EINECS No.** % TLV STEL **TWA PEL** STEL **IDLH** STEL PEAK **ETHYL METHACRYLATE** 97-63-2 OZ4550000 202-597-5 ≤ 90.0 NF NF NF (15)NA (10)NA NA 201-297-1 ≤ 5.0 HYDROXYPROPYL METHACRYLATE 27813-02-1 1004818HM NA NA NF NF NF NA NA NA OZ4400000 **GLYCOL HEMA-METHACRYLATE** 97-90-5 202-617-2 ≤ 5.0 NA NA NF NF NF NA NA NA **DIMETHYLTOLYLAMINE** 99-97-8 XU5803000 202-805-4 ≤ 1.0 NF NA NA NF NF NA NA NA 2440-22-4 GO6860000 219-470-5 NA NA NA NA **DROMETRIAZOLE** ≤ 1.0 NΑ NF NF NF 81-48-1 CB7700000 201-353-5 ≤ 1.0 NA NA NF NF NF NA NA NA VIOLET 2 4. FIRST AID MEASURES 4.1 First Aid: INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact Rocky Mountain Poison Control Center at 1-303-623-5716 or the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. IF problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the SKIN: affected area with plenty of soap and water. Do not wear contaminated clothing until after it has been properly cleaned. If irritation, redness or swelling persists, consult a physician immediately. INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration at once. Seek immediate medical attention. 4 2 Medical Conditions Aggravated by Exposure: 2 HEALTH Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, **FLAMMABILITY** 3 skin, respiratory system). REACTIVITY 2 PROTECTIVE EQUIPMENT В **EYES SKIN** 5. FIREFIGHTING MEASURES 5.1 Flashpoint & Method: 21°C (70°F) Autoignition Temperature: 5.2 ND Flammability Limits: 5.3 Lower Explosive Limit (LEL): ND Upper Explosive Limit (UEL): ND Fire & Explosion Hazards: This product is a flammable liquid. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO₂, NO_x). Extinguishing Methods 5.5 HazChem Code: 3WE Hazard Identification Number: 33 Water, Foam, CO₂, Dry Chemical 5.6 Firefighting Procedures First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering

storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated

equipment with soapy water before returning to service.

MATERIAL SAFETY DATA SHEET

Page 3 of 7

MSDS-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.0

MSDS Revision Date: 09/01/2008

6. ACCIDENTAL RELEASE MEASURES

6.1 Spil

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap & water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink, or smoke while handling this product.

7.2 Storage & Handling

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. Keep away from children at all times!

7.3 Special Precautions:

NA

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls:

Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).

8.2 Respiratory Protection:

No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

8.3 Eve Protection:

Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks.

8.4 Hand Protection

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals.

When handling large quantities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves.

8.5 Body Protection:

No apron required when handling small quantities.

When handling large quantities (e.g., \geq 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

MATERIAL SAFETY DATA SHEET

Page 4 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 FC Standards MSDS Revision: 3.0 MSDS Revision Date: 09/01/2008

Prep	ared to OSHA, ACC, AN	SI, NOHSC, WHMIS & 2001/58 EC Standards M	1SDS Revision: 3.0	MSDS Revision Date: 09/01/2008					
		9. PHYSICAL & CHEMICA	AL PROPERTIES						
.1	Density:	0.918							
.2	Boiling Point:	117 °C (243 °F)							
.3	Melting Point: NE								
.4	Evaporation Rate:	NA							
.5	Vapor Pressure:	NA							
.6	Molecular Weight:	NE							
.7	Appearance & Color:	Clear, colorless liquid with a mild acryl	lic odor.						
.8	Odor Threshold:	NE							
.9	Solubility:	Slightly soluble.							
0.10	рН	NA .							
0.11	Viscosity:	NE							
.12	Other Information:	Vapor density (air=1): > 1.0							
		1 2 2 2 2 7 7							
		10. STABILITY & REA	ACTIVITY						
0.1	Stability:	10. SIADILITI & KL	ACIIVIII						
0.1	,	ambient conditions when stored properly.							
0.2	Hazardous Decomposition Products:								
	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g.,								
	oxides of carbon & nitrogen).								
0.3	Hazardous Polymerization:								
	May occur.								
0.4	Conditions to Avoid: Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.								
) F	Incompatible Substances:								
0.5	1.5 Incompatible Substances: Strong oxidizers, peroxides, strong alkalis or acids.								
	Silong Oxidizers, peroxi	des, shong dikans of delas.							
		11. TOXICOLOGICAL II	NIEODAA ATIONI						
1.1	Todate Data	11. TOXICOLOGICAL II	NFORMATION						
1.1		neen tested on animals to obtain toxicological and in the scientific literature. These data have no							
1.2	Acute Toxicity: See Section 2.5								
1.3	Chronic Toxicity:								
	See Section 2.6								
1.4	Suspected Carcinogen: No								
1.5	Reproductive Toxicity:								
This product is not reported to produce reproductive toxicity in humans.									
	Mutagenicity: This product is not reported to produce mutagenic effects in humans. However, animal mutation data are available for the components of this product.								
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.								
	Teratogenicity: This product is not reported to produce teratogenic effects in humans.								
	Reproductive Toxicity: This product is not repo	rted to produce reproductive effects in humans.							
1.6	Irritancy of Product: See Section 2.3	near o produce reproducinte enecia in numuna.							
1.7	Biological Exposure Indices:								
11.8	Physician Recommendations: Treat symptomatically.								

MATERIAL SAFETY DATA SHEET

Page 5 of 7

MSDS-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 3.0 MSDS Revision Date: 09/01/2008 12. ECOLOGICAL INFORMATION Environmental Stability: This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Effects on Plants & Animals: 12.2 There is no specific data available for this product. 12.3 Effects on Aquatic Life: There is no specific data available for this product. Releases of large volumes may be harmful or fatal to overexposed aquatic life. Aquatic toxicity data for components of this product are available, but are not presented in this MSDS. 13. DISPOSAL CONSIDERATIONS Waste Disposal 13.1 Dispose of in accordance with all Federal, state, and local regulations. 13.2 U.S. EPA Characteristic Waste: D001 (flammable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. CONSUMER COMMODITY, ORM-D ($x \le 1.0 L$) UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II (x > 1.0 L) CONSUMER COMMODITY, 9, ID8000 ($x \le 0.5 L$) UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II (x > 0.5 L) 14.3 UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II, LTD QTY (x ≤ 1.0 L) SUMER COMMODITY UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II (x > 1.0 L) ORM-D 14.4 TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (x ≤ 1.0 L) UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II (x > 1.0 L) UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II, ADR, LTD QTY (x ≤ 1.0 L) UN2277, ETIL METILACRILATO, STABILIZADA, 3, II, CANTIDAD LIMITADA (x ≤ 1.0 L) 14.7 ADGR (AUS) UN2277, ETHYL METHACRYLATE, STABILIZED, 3, II

MATERIAL SAFETY DATA SHEET

Page 6 of 7

MSDS-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 3.0 MS

MSDS Revision Date: 09/01/2008

15. REGULATORY INFORMATION

SARA Reporting Requirements:

SARA 304 (Ethyl Methacrylate)

15.2 SARA Threshold Planning Quantity:

NA

15.1

15.3 TSCA Inventory Status:

All components of this product are listed in the TSCA Inventory or are exempt.

15.4 CERCLA Reportable Quantity (RQ):

Ethyl Methacrylate: 454 kg; 1000 lbs.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).

15.6 Other Canadian Regulations

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List (PSL). Class B2 Flammable Liquid.



15.7 State Regulatory Information

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List Delaware Air Quality Management List Massachusetts Hazardous Substances List New York List of Hazardous Substances Pennsylvania Hazardous Substances List Florida Right To Know List Ethyl Methacrylate Ethyl Methacrylate Ethyl Methacrylate Ethyl Methacrylate Ethyl Methacrylate Ethyl Methacrylate

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Ethyl Methacrylate: Flammable, Irritant (F, Xi). R: 11-36/37/38-43 – Highly flammable. Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. S: 2-9-16-29-33 – Keep out the reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not empty into drains. Take precautionary measures against static discharges. HAZCHEM CODE: 3WE



16. OTHER INFORMATION

16.1 Other Information

Precisely follow directions and MSDS (available through your supplier) for use. **Avoid all skin contact.** If redness or other signs of adverse reaction occur, discontinue use immediately. Use only in a well ventilated area. A ventilation system that expels vapors to the outdoors is recommended. Poisonous if swallowed! **Keep out of reach of children. FLAMMABLE!** Keep away from heat or flame. In case of emergency, contact your physician or local Poison Control Center immediately. FOR PROFESSIONAL USE ONLY.

16.2 Terms & Definitions

Please see last page of this MSDS.

16.3 Disclaimer

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $O \cdot P \cdot I$

16.5 Prepared by:

ShipMate, Inc. PO Box 787

Sisters, OR 97759-0787 USA Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700

e-mail: shipmate@shipmate.com



MATERIAL SAFETY DATA SHEET

Page 7 of 7

MSDS-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.0

MSDS Revision Date: 09/01/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDs. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL Permissible Exposure Limit	
IDLH Immediately Dangerous to Life and Health	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person					
	whose heart has stopped receives manual chest					
	compressions and breathing to circulate blood and provide					
	oxygen to the body.					


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4 Extreme Hazard	



PERSONAL PROTECTION RATINGS:







OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion		
Temperature	in air with no other source of ignition		
LEL	Lower Explosive Limit - lowest percent of vapor in air, by		
	volume, that will explode or ignite in the presence of		
	an ignition source		
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of		
	by volume, that will explode or ignite in the presence of		
	an ignition source		

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
-W -	Use No Water		
ОХ	Oxidizer		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o Or TC, TC _o , LC _{Io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL Canadian Non-Domestic Substance List	
PSL Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

		*	*		X	×	×
С	Е	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful