$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$
--

MATERIAL SAFETY DATA SHEET

Page 1 of 8

MSDS-053E

Prepa	ared to OSHA, ACC	C, ANSI, N	IOHSC, WHN	AIS & 2001/58	EC Standards	MS	SDS Revi	sion: 2	.0	MS	DS Rev	ision Da	ate: 11	/24/20	08
				1. PR		DENT	IFICA	TION							
1.1		T I I N I N I					CTUE			COLL	о тII				
1.0	OPI SOFT &			T NAIUK/	AL NAIL 3	KEIN	GINE	NEK	FOR	30LI	ĞΙΠ	IIN INA	AIL2		
1.2	Chemical Name: Solvent Mixture														
1.3	Synonyms:														
	NA														
1.4	Trade Names: NT111-EU														
1.5	Product Use:														
1.6	COSMETIC USE ONLY Distributor's Name:														
	OPI PRODUCTS, IN	NC													
1.7	Distributor's Address: 13034 SATICOY SI		HOLLYWOO	CA 91405	115 A										
1.8	Emergency Phone:	IKELI, NO		D, CA 71805	UJA										
	CHEMTREC: +1	1 (703) 5	527-3887 /	/ +1 (800) 4	24-9300										
1.9	Business Phone:														
	+1 (818) 759-2400	0 / +1 (800)) 341-9999												
				2 H	AZARD ID	FNTI	FICAT	ION							
2.1	Hazard Identification:			2 , 11											
	This product is Cl 1088 (2004)] and				NCE and as D	ANGE	ROUS G	OODS	accor	ding to	the clo	assificat	ion cri	teria o	f [NOHSC:
2.2	Routes of Entry:			Inhalatior	n: YE	S	Absor	ption:		YES	lr	ngestion	:	Y	ES
2.3	Effects of Exposure: INGESTION:	If my adva				aitin a a	nal/ard	i avrib a a						!	
	INGESTION:	ir produc	r is swallowe	a, may caus	e nausea, von	ning a	na/or a	lanned	a ana c	central r	iervou	s systen	n aepr	ession.	
	EYES:	Irritating t	o eyes. Syn	nptoms of ove	erexposure mo	ay inclu	de red	ness, it	ching,	irritatior	n and w	vatering	j .		
	SKIN:	May be in	ritating to sk	kin in some se	nsitive individ	uals, es	speciall	y after	prolon	ged an	d/or re	peated	conta	ict.	
					htly irritating t										
					ughing, whee tion 3 (Comp										
					ness, headach			greare			, cun	04000		nerre	
2.4	Symptoms of Overexpo									. .					
	Symptoms of skin cause redness, ite			ividuals may	include redne	ess, itch	ning, an	d irrita	tion of	affecte	d area	is. Ove	rexpos	ure in	eyes may
2.5	Acute Health Effects:	oning and	a marennig.												
	Mild to moderate		-	nd skin near	affected area	s. Ado	ditionall	y, high	conc	entratio	ns of v	apors o	can co	ause d	rowsiness,
2.6	dizziness, headac Chronic Health Effects:		nausea.												
	No chronic health		are known, d	although sym	otoms and dis	comfoi	t may a	occur fo	or seve	eral days	s follov	ving ove	erexpo	sure.	
2.7	Target Organs:														
	Eyes, skin and res	spiratory s	system.												
			2 00		ON & INC										
			J. C			JKED						IN AIR (r	ma /m3	•)	
							ACC	SIH		NOHSC		_	OSHA	<u> </u>	
							рр			ppm			ppm		OTHER
	CHEMICAL NAME	(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	TLV	STEL	IDLH	
ETHYL	ACETATE		141-78-6	AH5425000	205-500-4	≤ 40.0	400	NE	720	1440	NF	400	NE	2000	400 TWA
BUTYL	ACETATE		123-86-4	AF7350000	205-658-1	≤ 30.0	150	200	730	950	NF	200	200	1700	150 TWA
NITRO	CELLULOSE		9004-70-0	FJ6000000	NA	≤ 15.0	(10)	NE	NF	NF	NF	(10)	NE	NE	
ALCO	HOL DENATURED		64-17-5	KQ300000	200-578-6		1000	3000	1000	NF	NF	1000	3000	NA	ĺ

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

 $\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS

MSDS Revision: 2.0

		5. (ITION & II											
							100	2111	EXPO					³)	
							ACC			NOHSC ppm			DSHA ppm		OTHER
						0/			ES-	ES-	ES-				
	CHEMICAL NA	ME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	TLV		IDLH	
	ANE		142-82-5	MI7700000	205-563-8	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
	ROPYL ALCOHOL		67-63-0	NT8050000	200-661-7	≤ 5.0	400	500	983	1230	NF	400	500	2000	400 TW
FLAC	IC ACID/NEOPEN COL/TRIMELLITIC A OLYMER		28407-73-0	NA	NA	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
CR	LATES COPOLYM	ER	25133-97-5	NA	NA	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
RIPH	IENYL PHOSPHATE		115-86-6	TC840000	204-112-2	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
	ETHYL PENTANYL DBUTYRATE		6846-50-0	SA142000	229-937-9	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
	OSE ACETATE ISC	-	126-13-6	NA	204-771-6	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
	IYLENE GLYCOL (I MALDEHYDE)	IYDRATED	463-57-0	TY200000	207-339-5	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
OTHE		PRESENT IN L	ESS THAN 1%	CONCENTRAT	ION	BAL				MPONE ONAL H			ONTR	IBUTE	ANY
			1		ADDITIONAL II	NGREDIE	NTS		-						
CI 60	725		81-48-1	CB770000	201-353-5	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 26	100		13463-67-7	XR2275000	236-675-5	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
				4	FIRST AID	MFA	SIIRES								
4.1	First Aid:						JUNES								
	INGESTION:	offer plen	ty of water o	uce vomiting. r milk. Never ency number.	give water o	or milk to	o an une	consci	ous pe	erson. C	Contac	t the ne	earest	Poiso	n Contro
	EYES:			res, flush with ough irrigatio							ast 15	minute	s. O	pen c	ind clos
	SKIN:	and soap	. If irritation p	other signs of ersists, consul			develop	o, wasł	n affec	ted skii	n area	s with p	lenty	of wo	ırm wate
	INHALATION:		rictim to fresh	air at once.											
4.2	Medical Conditions	Aggravated by	Exposure:						HE/	LTH					1
	None known.								FLA	MMA	BILIT	Υ			3
															0
									PRC	DTECT	IVE E	QUI	°ME	NT	Α
												_			

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

		5. FIREFIGHTING ME	ASURES			
5.1	Flashpoint & Method: - 4 °C (24 °F) estimated.					
5.2	Autoignition Temperature:					
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	NE	Upper Explosive Li	mit (UEL):	NE
5.4	Fire & Explosion Hazards: WARNING: Flammable! Keep away fro closed.	m heat, lit cigarettes, sparks & o	pen flame.	Keep container	3	
5.5	Extinguishing Methods: CO2, Halon, Dry Chemical, Foam					0
5.6	Firefighting Procedures: This product is a Class IB flammable liqui oxides. Vapors of this product are heaving First responders should wear eye protecting fog to reduce or direct vapors. Water ma	er than air and may travel to a sou ion. Structural firefighters must we	rce of ignitic ar SCBAs an	on and flash back to d full protective equ	a leaking or op ipment. Use a w	en container.
	6	. ACCIDENTAL RELEASE	MEASU	RES		
6.1	Spills: Before cleaning any spill or leak, individ spills (e.g., <1 gallon) wear appropriate windows). Remove spilled material with properly in accordance with local, state water and soap. Remove any contaminor For spills ≥ 1 gallon, deny entry to all un product to containers for recovery or contaminated clothing promptly and wa sewers and open bodies of water.	personal protective equipment (e a absorbent material and place in and federal regulations. Wash all ited clothing and wash thoroughly protected individuals. Dike and disposal and solid diking mate	.g., goggles nto appropri affected ar before reus contain spill rial to sepo	, gloves). Maximize ate closed containe eas and outside of c e. with inert material (arate containers for	ventilation (ope er(s) for disposation container with pl e.g., sand or ea proper dispos	en doors and l. Dispose of enty of warm rth). Transfer al. Remove
	7. H	ANDLING & STORAGE I	NFORMA	TION		
7.1	Work & Hygiene Practices: Avoid prolonged contact with the produc ventilation, fans). After use, wash hands o					
7.2	Storage & Handling: Keep this material away from heat, spark when not in use. Empty container may care. Store containers in a cool, dry locc incompatible materials (see Section 10).	contain residual amounts of this p	product; the	efore, empty contai	iners should be	handled with
7.3	Special Precautions: Open containers slowly on a stable surf amounts of this product; therefore, empty	• • • •		in use. Empty con	tainers may cor	ntain residual

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.					
8.2	 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 					
8.3	Eye Protection: Depending on the use of this pr Canadian standards, or the Eur	oduct, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, opean Standard EN166.				
8.4		repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine r to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.				
8.5	Body Protection: No special body protection is re of Canada, the E.C. member st	equired under typical circumstances of use and handling. If necessary, refer to appropriate standards ates, or U.S. OSHA.				
		9. PHYSICAL & CHEMICAL PROPERTIES				
9.1	Density:	0.96				
9.2	Boiling Point:	NA				
9.3	Melting Point:	NE				
9.4	Evaporation Rate:	NA				
9.5	Vapor Pressure:	NA				
9.6	Molecular Weight:	NE				
9.7	Appearance & Color:	Viscous liquid				
9.8	Odor Threshold: ND					
9.9	Solubility:	Insoluble				
9.10	рН	NA				
9.11	Viscosity:	>1200 cPs				
9.12	Other Information:	NA				
		10. STABILITY & REACTIVITY				
10.1	 Stability: This product is stable under ambient conditions when stored properly (see Section 7, Storage and Handling). 					
10.2	 Hazardous Decomposition Products: If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gasses (e.g., CO, CO₂) 					
10.3	Hazardous Polymerization: May occur, if exposed to extrem	mely high temperatures.				
10.4		t and direct sunlight. This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), or muriatic acids), strong bases (e.g., lye, potassium hydroxide).				
10.5	Incompatible Substances: None known.					

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

	11. TOXICOLOGICAL INFORMATION
11.1	Toxicity Data: The product has NOT been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. This data has not been presented in this document.
11.2	Acute Toxicity: See section 2.5
11.3	Chronic Toxicity: See section 2.6
11.4	Suspected Carcinogen: This product contains Isopropyl Alcohol which is not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC.
11.5	Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity: This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity: This product is not reported to produce teratogenic effects in humans.
	Reproductive Toxicity: This product is not reported to produce reproductive effects in humans.
11.6	Irritancy of Product: See Section 2.3
11.7	Biological Exposure Indices: NE
11.8	Physician Recommendations: Treat symptomatically.
	12. ECOLOGICAL INFORMATION
12.1	Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows:
	<u>Ethyl Acetate</u> : Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
	<u>Butyl Acetate</u> : Koc = 1.82. Water solubility: 120 parts H ₂ O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
	<u>Isopropyl Alcohol</u> : Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals: There is no specific data available for this product.
12.3	Effects on Aquatic Life: There is no specific data available for this product; however, very large release of this product may be harmful or fatal to overexposed aquatic life.
	13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:
13.2	Dispose of in accordance with federal, state and local regulations. Special Considerations:
	U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

		TION INFORMATION	
	pasic description (ID Number, proper shipping name, hazard cla: tional descriptive information may be required by 49 CFR, IATA/I		ch mode of transportation.
14.1	49 CFR (GND):		
	CONSUMER COMMODITY, ORM-D (≤ 1.0 L)		
	UN1263, PAINT, 3, II (> 1.0 L)		
14.2	IATA (AIR):		
	CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)		
	UN1263, PAINT, 3, II (> 0.5 L)		
14.3	IMDG (OCN):		
	UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L)		CONSUMER COMMODITY
	UN1263, PAINT, 3, II (> 1.0 L)		ORM-D
14.4	TDGR (Canadian GND):		CTIM-D
	MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "L	TD QTY" or "QUANT LTEE" (≤ 1.0 L)	ONNO LANKINITRA CHCADOX NINI
	UN1263, PAINT, 3, II (> 1.0 L)		
14.5	ADR/RID (EU):		
	UN1263, PAINT, 3, 3 °(b), ADR, LTD QTY (≤ 1.0 L)		
14.6	SCT (MEXICO):		
	UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (≤	1.0 L)	
14.7	ADGR (AUS):		
	UN1263, PAINT, 3, 3 °(b), LTD QTY (≤ 1.0 L)		
	15. REGULATO	RY INFORMATION	
15.1	SARA Reporting Requirements: SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate, Is	sopropyl Alcohol.	
15.2	SARA Threshold Planning Quantity: There are no specific Threshold Planning Quantities for the corr	ponents of this product.	
15.3	TSCA Inventory Status: All chemical substances of this product are listed on the TSCA i	inventory or are otherwise exempted from ir	nventory status.
15.4	CERCLA Reportable Quantity (RQ): Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.		
15.5	Other Federal Requirements: This product complies with the appropriate sections of the Food	d and Drug Administration's 21 CFR subchap	ter G (Cosmetics).
15.6	Other Canadian Regulations: This product has been classified according to the hazard crite the information required by the CPR. The components of this p the components of this product are listed on the Priorities Subst	roduct are listed on the DSL/NDSL. None of	
15.7	State Regulatory Information: Ingredients in this mixture on found on the following state criter	ia lists:	
	California OSHA Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropano	
	Delaware Air Quality Management List	Butyl Acetate, Ethyl Acetate, Nitrocellulo	
	Massachusetts Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropano	
		Nitrocellulose	
	Minnesota Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropano	I
	New Jersey Right to Know Hazardous Substances List	Isopropanol, Nitrocellulose	
	New York List of Hazardous Substances	Butyl Acetate, Ethyl Acetate,	
	Pennsylvania Hazardous Substances List	Butyl Acetate, Ethyl Acetate, isopropano	
	Washington Permissible Exposure Limits for Air Contaminants	Butyl Acetate, Ethyl Acetate, Isopropano Triphenyl Phosphate Ethyl Acetate	Ι,
L	Wisconsin Hazardous Substances List		

 $\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

15.8

16.1

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

15.	REGULATORY INFORMATION- continued	
67/548/EEC (European Union) Requirements:		

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC: <u>Butyl Acetate</u>: Flammable (F). R: Flammable. S: 9-16-33 -Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. <u>Ethyl Acetate</u>: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges. Do not empty into drains. Take precautionary measures against static discharges.

16. OTHER INFORMATION

EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. **KEEP OUT OF REACH OF CHILDREN.**

16.2 Terms & Definitions: Please see last page of this MSDS

Other Information

16.3 Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA (818) 759-2400 phone (818) 759-5770 fax	O·P·I
16.5	http://www.opi.com/ Prepared by: ShipMate, Inc. 780 Buckaroo Trail, Suite D Sisters, OR 97759-0787	ShipMate Durantis Grade
	+1 (310) 370-3600 phone +1 (310) 370-5700 fax http://www.shipmate.com/	Dangerous Goods Training & Consulting

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-053E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Numbe
CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists			
TLV	Threshold Limit Value			
OSHA	OSHA U.S. Occupational Safety and Health Administration			
PEL	Permissible Exposure Limit			
IDLH	Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	---

HEALTH

FLAMMABILITY

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	FLAMMABILIT
1	Slight Hazard	
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	Ś		G	Ś	÷.	Ň	
в	\$		н	1	S.		%
с	\$	~ _	I	Ś	S.	¥	
D	🔁 🗳	~	J	()	j.		¥
E	\$		к		٩	⋪	L
F	\$	- -	x			pervisor ndling dire	
Sa	fety Glasses	Splash Goggles		e Shield & Protection		Glove	A S
	iery orasses	opiasii ooggics	Ever	rolection	1	0.011	
	L	~		⋪			•
	Boots	Synthetic Apron	F	ull Suit		Dust Resp	oirator
			F	Se la ce		Airlin	ĺ
Var	oor Respirator	Dust & Vapor Respirator		spirator		Airiin Hood/Mo	-
1 ar		Respirator	ĸe	spirator		nooa/Ma	USK OF
	$\left(\begin{array}{c} \end{array} \right)$	Note: the dotted protective equipme					

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				


or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus
JCDA	ser contained breating apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ох	Oxidizer



TOXICOLOGICAL INFORMATION:

LD50	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC50	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TDio	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic					
TC, TC _o , LC _{io} , & LC _o	effects					
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TLm	Median threshold limit					
log Kow or log Koc	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
CPR	Canada's Controlled Product Regulations

EC INFORMATION:

V		×	¥	8	X	×	×
С	E	F	Ν	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

WHMIS INFORMATION:

