$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$
--

Page 1 of 8

U					JAILI								MSD	S-06	4G
Prepa	ared to OSHA, AC	C, ANSI, NO	HSC, WHMIS	& 2001/58 EC	Standards	MSDS Re	evision	: 2.0		MSDS	Revisio	n Date	e: 04/28	8/2010	
				1. PRO	DUCT IDEI	NTIFIC	ATIC	N							
1.1				۸T											
1.2	OPI NATURA	AL NAIL	DAJE CU	AI											
1.2	Solvent Mixture														
1.3	Synonyms:														
1.4	NA Trade Names:														
	NTT10 NTT14														
1.5	Product Use: COSMETIC USE ONLY														
1.6	Distributor's Name:														
	OPI PRODUCTS, IN	NC													
1.7	Distributor's Address: 13034 SATICOY S	TREET, NO. H	IOLLYWOOD,	CA 91605 USA	A										
1.8	Emergency Phone:		· ·												
	CHEMTREC: +1	1 (703) 52	27-3887 / +	1 (800) 424	-3887										
1.9	Business Phone: +1 (818) 759-2400	0 / +1 (800)-	-341-9999												
		, <u>(</u> <u>/</u>													
				2. HAZ	ARD IDEN	ITIFIC/	ATIO	Ν							
2.1	Hazard Identification:														
	This product is c (2004) and ADG (ind as dange	rous goo	ods ac	cordin	g to th	ie clas	sificati	on cri	eria o	f NOH	SC:1088
2.2	Routes of Entry:			Inhalation: Y	S NO	Abs	orptior	ו:	YE	5	Inges	stion:		YES	
2.3	Effects of Exposure:	If you also also at the				a. a.a.d./a	استا ما								
		•		•	ausea, vomitin cposure may i	•					-		lepres	sion.	
		-			ive individuals				-			-	ontact	•	
					r irritating to th										
					ing, wheezing 1 3 (Composil										
2.4			(e.g., drowsi	ness, dizziness	, headaches,	nausea)	•								
2.4	Symptoms of Overexpo Symptoms of skir		sure in individ	luals may incl	lude redness,	itching,	and irri	itation	of affe	cted a	reas.	Overex	posur	e in ey	es may
	cause redness, it	-		•		0.							•		
2.5	Acute Health Effects: Mild to moderate	e irritation t	o eves and s	skin near affe	cted areas.	Addition	allv. hi	ah co	ncentro	ations	of vap	ors ca	n cau	se dro	wsiness
	dizziness, headad	ches and no					,,	3							
2.6	Chronic Health Effects: None Known.														
2.7	Target Organs:														
	Eyes, skin and res	spiratory sys	stem.												
			3 COM		N & INGR				ΛΤΙΟ						
			J. COM								IMITS II	N AIR (mg/m [:]	3)	
								GIH		NOHSC			OSHA		
							pr P	om 	ES-	ppm ES-	ES-		ppm		OTHER
	CHEMICAL NAME		CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK		STEL	IDLH	
	ACETATE		141-78-6	AH5425000	201-550-6	≤ 30.0	400	400	200	400	NF	NA	NA	2000	400 TW
	HOL DENATURED (S HOL-40B)	U .	64-17-5	KQ300000	200-578-6	≤ 30.0	1900	NA	1880	NF	NF	1000	NA	NA	
	ACETATE		123-86-4	AF7350000	204-658-1	≤ 25.0	150	200	150	200	NF	200	200	1700	150 TW
		-t D-t												<u> </u>	

NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

 $\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS

MSDS Revision: 2.0

MSDS Revision Date: 04/28/2010

3. COMPOSITION & INGREDIENT INFORMATION - continued EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA OTHER ppm ppm ppm ES-ES-ES-% **RTECS No.** TLV TWA CAS No. **EINECS No.** STEL PEAK PEL STEL IDLH CHEMICAL NAME(S) STEL HEPTANE 142-82-5 MI7700000 205-563-8 400 1640 ≤ 10.00 NA 2050 NF 500 NA NA NITROCELLULOSE 9004-70-0 FJ600000 ≤ 10.0 NF NA NA NA NF NF NA NA NA TOSYLAMIDE EPOXY RESIN 130353-62-7 NF NF NF NA NA ≤ 5.0 NA NA NA NA NA 1230 2000 400TWA ISOPROPYL ALCOHOL 67-63-0 NT8050000 200-661-7 400 500 983 NF 400 500 ≤ 5.0 TRIMETHYL PENTANYL 6846-50-0 SA142000 229-937-9 NA ≤ 3.0 NA NA NF NF NF NA NA DIISOBUTYRATE POLYVINYL BUTYRAL 63148-65-2 TR49550000 NA ≤ 3.0 NA NF NF NF NA NA NA NA CAMPHOR 76-22-2 EX1225000 NA ≤ 2.0 NA NA NF NF NF NA NA NA BENZOPHENONE-1 131-56-6 DJ0700000 205-029-4 ≤ NF 1.0 NA NA NF NF NA NA NA DIMETHICONE 6009-65-9 NA 63148-62-9 N 1.0 NA NA NF NF NF NA NA NA QJ197000 CI 17200 3567-66-6 222-656-9 NA NA NA NF NF NF NA NA NA 81-48-1 CI 60725 CB7700000 201-353-5 NA NA NA NF NF NF NA NA NA 4. FIRST AID MEASURES 4.1 First Aid INGESTION: If ingested, do not induce vomiting. Drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer plenty of water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time and amount of the substance that was swallowed. EYES: If product is in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If problem persists, consult a physician. SKIN: If redness, dryness or other signs of irritation to the skin develop, wash affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician. Remove victim to fresh air at once. INHALATION: 4.2 Medical Conditions Aggravated by Exposure: HEALTH 1 None known. 3 FLAMMABILITY REACTIVITY 0 **PROTECTIVE EQUIPMENT** Α **EYES**

0·P·	Ι
------	---

Page 3 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 04/28/2010

		5. FIREFIGHTING MI	EASURES						
5.1	Flashpoint & Method: - 1 °C (30 °F) estimated.								
5.2	Autoignition Temperature:								
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	NE	Upper Explosive	e Limit (UEL):	NE			
5.4	Fire & Explosion Hazards: WARNING: Flammable! Keep away fre closed.	om heat, lit cigarettes, sparks &	open flame	e. Keep container					
5.5	Extinguishing Methods: CO2, Halon, Dry Chemical, Foam					0			
5.6	Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.								
	6	. ACCIDENTAL RELEAS	E MEASU	JRES					
6.1	Spills: Before cleaning any spill or leak, individ spills (e.g., <1 gallon) wear appropriate windows). Remove spilled material with properly in accordance with local, state water and soap. Remove any contain	personal protective equipment (h absorbent material and place and federal regulations. Wash c ated clothing and wash thorough	e.g., goggle into approp Ill affected c Ily before re	es, gloves). Maximiz vriate closed contain areas and outside of use.	e ventilation (o ner(s) for dispos container with	pen doors and al. Dispose of plenty of warm			
	For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.								
				471011					
	/. H	ANDLING & STORAGE	INFORM	AIION					
7.1	Work & Hygiene Practices: Avoid prolonged contact with the proc exhaust ventilation, fans). After use, we product.								
7.2	Storage & Handling: Keep this material away from heat, spar when not in use. Empty container may care. Store containers in a cool, dry loco incompatible materials (see Section 10).	contain residual amounts of this ation, away from direct sunlight, o	product; the	erefore, empty cont	ainers should be	e handled with			
7.3	Special Precautions: Open containers slowly on a stable sur amounts of this product; therefore, empt	• • • •		ot in use. Empty co	ntainers may c	ontain residual			
L									

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 04/28/2010

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	eyewash station, sink or washbasin is available in case of exposure to eyes.								
8.2	 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 								
8.3	Eye Protection:								
8.4	Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.								
8.5	 Body Protection: 8.5 Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 								
		9. PHYSICAL & CHEMICAL PROPERTIES							
9.1	Density:	0.9980 TO 1.0008							
9.2	Boiling Point:	NA							
9.3	Melting Point: NE								
9.4	Evaporation Rate:	NA							
9.5	Vapor Pressure:	NA							
9.6	Molecular Weight:	NE							
9.7	Appearance & Color:	Viscous liquid							
9.8	Odor Threshold:	ND							
9.9	Solubility:	Insoluble							
9.10	рН	NA							
9.11	Viscosity:	>1200							
9.12	Other Information:	NA							
		10. STABILITY & REACTIVITY							
10.1	Stability: This product is stable under am	bient conditions when stored properly (see Section 7, Storage and Handling).							
10.2	Hazardous Decomposition Products: If exposed to extremely high t gasses (e.g., CO, CO ₂)	emperatures, the products of thermal decomposition may include irritating vapors and carbon oxide							
10.3	Hazardous Polymerization: May occur, if exposed to extrem	mely high temperatures.							
10.4		t and direct sunlight. This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), or muriatic acids), strong bases (e.g., lye, potassium hydroxide).							
10.5	Incompatible Substances: None known.								
	NONE KNOWN.								

Page 5 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 04/28/2010 11. TOXICOLOGICAL INFORMATION 11.1 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity See Section 2.5 11.3 Chronic Toxicity See Section 2.6 11.4 Suspected Carcinogen: This product contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as Group 3 carcinogens by the IARC. 11.5 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. 11.6 Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indices: NE 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals: There is no specific data available for this product. Effects on Aquatic Life 12.3 There is no specific data available for this product; however, very large release of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal Dispose of in accordance with federal, state and local regulations. 13.2 Special Considerations U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 04/28/2010

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND): EXCEPTED QUANTITY (49 CFR §173.4a) (≤ 30 ml) CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)	\square
14.2	IATA (AIR): EXCEPTED QUANTITY (AIR SHIPPER § 4.1.2) (≤ 30 ml) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 0.5 L)	**
14.3	IMDG (OCN): EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)	ORM-D
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)	
14.5	ADR/RID (EU): UN1263, PAINT RELATED MATERIAL, 3, II, ADR	
14.6	MEXICO (SCT): UN1263, PRODUCTOS PARA PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)	UN1263
14.7	ADGR (Australia): UN1263, PAINT RELATED MATERIAL, 3, II, ADR	
		FLAMMABLE LIQUID
		•
	15. REGULATORY INFORMATION	
15.1	SARA Reporting Requirements: SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate, Isopropyl Alcohol	
15.2	SARA Threshold Planning Quantity: There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status: All chemical substances of this product are listed on the TSCA inventory or are otherwise exempted from in	ventory status.
15.4	CERCLA Reportable Quantity (RQ): Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.;	
15.5	Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchap	ter G (Cosmetics).
15.6	Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.	

C)·P·I	MAT	ERIAL SAFE	ETY	OATA SHE	ET	Page 7 of 8 MSDS-064G	
Prepa	ared to OSHA, ACC	. ANSI, NOHSC, WHMIS	& 2001/58 EC Standards		MSDS Revision: 2.0	MSDS Revision	Date: 04/28/2010	
	·							
		15. RE	EGULATORY INFO	RM/	ATION - continued			
15.7	State Regulatory Inform Ingredients in this		e following state criteria I	lists:				
	California OSHA Hazardous Substances ListButyl Acetate, Ethyl Acetate, IsopropanolDelaware Air Quality Management ListButyl Acetate, Ethyl Acetate, Nitrocellulose,Massachusetts Hazardous Substances ListButyl Acetate, Ethyl Acetate, Nitrocellulose,Minnesota Hazardous Substances ListEthanol, Butyl Acetate, Ethyl Acetate, IsopropanolNew Jersey Right to Know Hazardous SubstancesIsopropanol, NitrocelluloseNew York List of Hazardous SubstancesButyl Acetate, Ethyl Acetate, IsopropanolNew York List of Hazardous SubstancesButyl Acetate, Ethyl AcetatePennsylvania Hazardous Substances ListButyl Acetate, Ethyl Acetate,Washington Permissible Exposure Limits for Air ContaminantsButyl Acetate, Ethyl Acetate, Isopropanol, HeptateWisconsin Hazardous Substances ListButyl Acetate						ol, Camphor, Heptane ol, Camphor, Heptane	
15.8								
16.1	Other Information:		16. OTHER IN	FOR	RMAIION			
10.1	EXTREMELY FLAMI thoroughly with ru	unning water. Use only	in a well-ventilated area	a. If re	as directed. Avoid eye c edness or other signs of ad [.] OF REACH OF CHILDREN.			
16.2	Terms & Definitions: Please see last pc	ige of this MSDS.						
16.3								
16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Stre No. Hollywood, C +1 (818) 759-2400 +1 (818) 759-5770 http://www.opi.co	eet A 91605 USA phone fax	O·P·I					
16.5	Prepared by: ShipMate, Inc. P.O. BOX 787 Sisters, OR. 97759- 310-370-3600 pho 310-370-5700 fax http://www.shipm	ne	ShipM Dangerou Training d	is Goods				

 $\mathbf{0} \cdot \mathbf{P} \cdot \mathbf{I}$

Page 8 of 8

MSDS-064G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 04/28/2010

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Numl
--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	---

HEALTH

FLAMMABILITY

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	FLAMMABILIT
1	Slight Hazard	
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	Ś		G	Ś	 A state 	N	
в	\$	l,	н	()	Ő.	~	%
с	\$	v v	I	Ś	ő,	¥,	
D		· ···	J	6	S.		¥
E	\$		к	Ĵ	ő,	X	L
F	\$	V 📥 🚭	×			pervisor ndling dire	
Sa	Fety Glasses	Splash Goggles		e Shield 8 Protection		Glove	es
	l	-print e eggen	Lvei				}
	Boots	Synthetic Apron	F	ull Suit		Dust Resp	, pirator
	*	Dust & Vapor	Fu	W Face		Airlin	
Vap	oor Respirator			spirator		Hood/Mo	-
	$\left(\begin{array}{c} \end{array} \right)$	Note: the dotted protective equipm					

piratory trations or for large volume spills or releases of product.


FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
Lower Explosive Limit - lowest percent of vapo volume, that will explode or ignite in the prese ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

OTHER STANDARD ABBREVIATIONS:

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ох	Oxidizer



TOXICOLOGICAL INFORMATION:

LD50	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s								
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal								
ppm	Concentration expressed in parts of material per million parts								
TDio	Lowest dose to cause a symptom								
TCLo	Lowest concentration to cause a symptom								
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic								
TC, TC _o , LC _{io} , & LC _o	effects								
IARC	International Agency for Research on Cancer								
NTP	National Toxicology Program								
RTECS	Registry of Toxic Effects of Chemical Substances								
BCF	Bioconcentration Factor								
TLm	Median threshold limit								
log Kow or log Koc	Coefficient of Oil/Water Distribution								

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
CPR	Canada's Controlled Product Regulations

EC INFORMATION:

V		×	*	8	X	×	×
С	E	F	Ν	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

WHMIS INFORMATION:

