### MATERIAL SAFETY DATA SHEET

Page 1 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0 MSDS Revision Date: 08/23/2011 1. PRODUCT IDENTIFICATION Product Name: OPI NAIL LACQUER 1.2 Chemical Name: **SOLVENT MIXTURE** 1.3 Synonyms: NA 1.4 Trade Names NL\*\*\* (Various Colors) 1.5 Product Use COSMETIC USE ONLY 1.6 Manufacturer's Name OPI PRODUCTS, INC. 1.7 Manufacturer's Address 13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA 1.8 Emergency Phone CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 1.9 +1 (818) 759-2400 / +1 (800)-341-9999 2. IDENTIFICATION OF RISKS This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). Flammable liquid. Hazard Statements: H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation. Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces — No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **HAZCHEM CODE: 3YE** Poison Schedule: None Allocated. Routes of Entry: 2.2 Inhalation: YES Absorption: YES YES Inaestion: 2.3 Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). 2.4 Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. 2.5 Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 2.6 Chronic Health Effects None known. 2.7 Target Organs: Eyes, skin and respiratory system. NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format

## **MATERIAL SAFETY DATA SHEET**

Page 2 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

	3. CO/	MPOSITIO	N & INGR	EDIEN1	[ INF	ORM	ATIC	N					
									MITS IN	AIR (	mg/m³	3)	
					AC	GIH	NOHSC				OSHA		
					pp	m		ppm			ppm	ı	OTHER
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	> 25.0	400	400	200	400	NF	NA	NA	2000	400 TWA
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	> 24 .0	150	200	150	200	NF	200	200	1700	150 TWA
NITROCELLULOSE	9004-70-0	QW0970000	NA	> 12.0	(10)	NE	NF	NF	NF	(10)	NE	NE	
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	> 10.0	200	250	835	1040	NF	200	250	NA	
TOSYLAMIDE/FORMALDEHYDE RESIN	1338-51-8	NA	NA	> 9.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	> 5.0	400	500	983	1230	NF	400	500	2000	400TW A
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	≥ 3.0	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENYL PHOSPHATE	115-86-6	TC8400000	NA	≥ 3.0	(3)	NA	(3)	NF	NF	(3)	NA	NA	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	≥ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CAMPHOR	76-22-2	EX1225000	200-945-0	≥ 1.0	(2)	NE	2	NF	NF	(2)	NE	NE	
STEARALKONIUM BENTONITE	71011-24-0	NA	NA	≥ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	(15)DU ST
DIACETONE ALCOHOL	123-42-2	SA9100000	204-626-7	< 1.0	240	NA	238	NF	NF	240	1800	NA	
STEARALKONIUM HECTORITE	94891-33-5	NA	275-126-4	< 0.50	NA	NA	NF	NF	NF	NA	NA	NA	
BENZOPHENONE-1	131-56-6	DJ0700000	205-029-4	< 0.10	NA	NA	NF	NF	NF	NA	NA	NA	
CITRIC ACID	77-92-9	GE7350000	201-069-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIMETHICONE	9006-65-9	TY2000000	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
		MAY CO	NTAIN ADDITIO	NAL INGR	EDIENTS	S							
MICA	12001-26-2	VV8760000	310-127-6	≤ 1.0	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC
POLYETHYLENE TEREPHTHALATE	25038-59-9	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM SODIUM BOROSILICATE	65997-17-3	NA	266-046-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM ALUMINUM BOROSILICATE	65997-17-3	NA	266-046-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ALUMINA	1344-28-1	BD1200000	215-691-6	≤ 1.0	(10)	NA	(5)	NF	NF	(15)	NA	NA	(5) DUST
SILICA	7631-86-9	NA	231-545-4	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
HYDROGENATED POLYISOBUTYLENE	68937-10-0	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
PALMITIC ACID	57-10-3	RT4550000	200-312-9	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIAMOND	7782-40-3	HL4158550	231-953-2	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
TIN OXIDE	18282-10-5	XQ4000000	242-159-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SYNTHETIC FLUORPHLOGOPITE	12003-38-2	NA	234-426-5	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SD ALCOHOL 40B	64-17-5	KQ6300000	200-578-6	≤ 1.0	1000	3000	1000	NF	NF	1000	3000	NE	
ADIPIC ACID / NEOPENTYL GLYCOL /TRIMELLTIC ANHYDRIDE COPOLYMER	28407-73-0	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
STYRENE/ACRYLATES COPOLYMER	NA	NA	NA	< 1.0									
CI 77120 (BARIUM SULFATE)	7727-43-7	CR0600000	231-784-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77163 (BISMUTH OXYCHLORIDE)	7787-59-9	EB2700000	232-122-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77891 (TITANIUM DIOXIDE)	13463-67-7	XR2275000	236-675-5	< 1.0	10	NA	NF	NF	NF	10	NA	NA	
N-BUTYL ALCOHOL	71-36-3	EO1400000	200-751-6	< 1.0	NA	NA	152	NF	NF	300	NA	NA	SKIN
ACRYLATES COPOLYMER	25133-97-5	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	SKIIN
				11.0		1.7	<b></b> -					.,,	<b>-</b>

## **MATERIAL SAFETY DATA SHEET**

Page 3 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards	MSDS Revision: 4.0	MSDS Revision Date: 08/23/2011
--	--------------------	--------------------------------

		3. C	OMPOSI	TION & IN	GREDIENT	INFO	RMA	TION	l - co	ontin	ved				
				1							MITS IN	AIR (	mg/m <sup>3</sup>	3)	
							AC	GIH		NOHSC			OSHA	_	
							pp	m		ppm			ppm		OTHER
	CHEMICAL NA	ME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- Stel	ES- PEAK	PEL	STEL	IDLH	
THY	LENE/VA COPOL	LYMER	24937-78-8	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77	491 (IRON OXID	ES)	1309-37-1	NO740000	215-168-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77	499 (IRON OXID	ES)	1317-61-9	NA	215-277-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77	510 (FERRIC FER	ROCYANIDE)	14038-43-8	LJ8200000	237-875-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	140 (YELLOW 5)		1934-21-0	UQ6400000	217-699-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 47	005 (YELLOW 10	)	8004-92-0	GC5796000	305-897-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15	850 (RED 6)		NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15	850 (RED 7)		5858-81-1	QJ1975000	227-497-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
JI 73	360 (RED 30)		2379-74-0	NA	219-163-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15	880 (RED 34)		6417-83-0	NA	229-142-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 42	.090 (BLUE1)		3844-45-9	BQ4725000	223-339-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77	000 (ALUMINUM	POWDER)	7429-90-5	BD0330000	231-072-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
JI 75	170 (GUANINE)		73-40-5	MF8260000	200-799-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60	725 (VIOLET 2)		81-48-1	CB7700000	201-353-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	007 (ULTRAMAR	INES)	1302-83-6	NA	215-111-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77	266 (BLACK 2)		1333-86-4	NA	215-609-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
4.1	First Aid: INGESTION:  EYES: SKIN:	patient is vonearest Pois ingested an Splashes are minutes. If i	omiting, contion Control Contr	e vomiting. If nue to offer wenter or local of the substar owever, if process, contact a poduct is on the ap and water.	ater or milk. emergency nonce that was soluct gets in the hysician. e skin, rinse the	neen swa Never g umber. wallowed e eyes, fl	allowed ive wa Provided d. ush with	ter or e an e h copi	milk to stimate ous an rm wa	an une of the nounts	nconso e time of luke lowed	ious p at whi warm by a t	erson. ch the water horoug	Cont mater for at l	act the ial was east 15
	INHALATION:	Remove vic	tim to fresh a	r at once.											
4.2	Medical Condition  None known.	ns Aggravated by	Exposure:						HEAL	TH					1
	HOHE KHOWII.								FLAN	MA	BILIT'	Υ			3
									PHYS	ICA	L HA	ZARI	DS		0
									PRO1						A
								<b>!</b>	EYES	<u> </u>				<del></del>	-

### MATERIAL SAFETY DATA SHEET

Page 4 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

#### 5. FIREFIGHTING MEASURES

5.1 Flashpoint & Method:

-4 °C (24 °F) estimated.

5.2 Autoignition Temperature

NA

5.3

Flammability Limits:

Lower Explosive Limit (LEL):

NE

Upper Explosive Limit (UEL):

NE

Fire & Explosion Hazards:

WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.

Extinguishing Methods


HazChem Code: 3YE

Hazard Identification Number: 33 CO<sub>2</sub>, Halon, Dry Chemical, Foam

5.6 Firefighting Procedures

> This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

> First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



#### 6. ACCIDENTAL RELEASE MEASURES

6.1

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

#### 7. HANDLING & STORAGE INFORMATION

7.1

Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7.2 Storage & Handling:

> Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

7.3 Special Precautions:

> Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

### MATERIAL SAFETY DATA SHEET

Page 5 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0 MSDS Revision Date: 08/23/2011 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 8 1 Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.2 No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8 4 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.5 No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Density: 0.9998 9.2 Boiling Point: 171 - 640°F 93 Meltina Point: NE 9.4 **Evaporation Rate** NA 9.5 Vapor Pressure: NA 9.6 Molecular Weight: NE 9.7 Appearance & Color Viscous liquid, various colors 9.8 Odor Threshold ND 99 Solubility: Insoluble 9.10 На 9.11 Viscosity > 1200 cPs 9.12 Other Information NA 10. STABILITY & REACTIVITY 10.1 Stable under ambient conditions when stored properly (see Section 7, Storage and Handling) 10.2 Hazardous Decomposition Products If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO<sub>2</sub>). 10.3 Hazardous Polymerization May occur, if exposed to extremely high temperatures. 10.4 This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). Incompatible Substances None known.

### **MATERIAL SAFETY DATA SHEET**

Page 6 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0 MSDS Revision Date: 08/23/2011 11. TOXICOLOGICAL INFORMATION Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. See Section 2.5 Chronic Toxicity: 11.3 See Section 2.6 11.4 Suspected Carcinogen This product contains Isopropyl Alcohol which is not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC. 11.5 This product is not reported to produce reproductive effects in humans. This product is not reported to produce mutagenic effects in humans. This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.6 Irritancy of Product: See Section 2.3 Biological Exposure Indices: Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate:  $K_{OC}$  = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H<sub>2</sub>O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

 $0.9 \cdot 1$ 

### MATERIAL SAFETY DATA SHEET

Page 7 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011


#### 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

49 CFR (GND) EXCEPTED QUANTITY (49 CFR §173.4a) (≤ 30 ml) CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L) IATA (AIR) 14 2 EXCEPTED QUANTITY (AIR SHIPPER § 4.1.2) (≤ 30 ml) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 0.5 L)



14.3 EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L)



UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L) 14.5

UN1263, PAINT RELATED MATERIAL, 3, II, ADR

14.6 MEXICO (SCT)

UN1263, PRODUCTOS PARA PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)

14.7

UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L)







#### 15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements

> This material contains Butyl Acetate, Ethyl Acetate, Isopropanol, and n-Butyl alcohol, which are subject to the reporing requirement of Section 131 of SARA Title III and 40 CFR Part 373

15.2 SARA Threshold Planning Quantity

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ)

Butyl Acetate: 5000 lbs.; 2270 kg. Ethyl Acetate: 5000 lbs; 2270 kg. Acetone: 5000 lbs; 2270 kg.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)

15.6 Other Canadian Regulations:

> This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



### MATERIAL SAFETY DATA SHEET

Page 8 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

#### 15. REGULATORY INFORMATION - continued

15.7 State Regulatory Information:

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List Delaware Air Quality Management List Massachusetts Hazardous Substances List

Minnesota Hazardous Substances List

New Jersey Right to Know Hazardous Substances List

New York List of Hazardous Substances Pennsylvania Hazardous Substances List

Washington Permissible Exposure Limits for Air Contaminants

Wisconsin Hazardous Substances List

Butyl Acetate, Ethyl Acetate, Isopropanol, acetone

Butyl Acetate, Nitrocellulose, Ethyl Acetate

Butyl Acetate, Nitrocellulose, Ethyl Acetate, Isopropanol,

Camphor, Triphenyl Phosphate, acetone

Butyl Acetate, Ethyl Acetate, Isopropanol, Camphor,

Triphenyl Phosphate, acetone

Isopropanol, acetone Butyl Acetate, Ethyl Acetate

Butyl Acetate, Ethyl Acetate, Isopropanol, Camphor,

Triphenyl Phosphate, acetone

Butyl Acetate, Ethyl Acetate, Isopropanol, Triphenyl Phosphate

**Ethyl Acetate** 

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

Hazard Statements: H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation.

Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces — No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

<u>Butyl Acetate</u>: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Hazard Statements: H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation.

Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces — No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

<u>Isopropanol</u>: Flammable (F). R: 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

HAZCHEM CODE: 3[Y]E Poison Schedule: None





### **MATERIAL SAFETY DATA SHEET**

Page 9 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

#### 16. OTHER INFORMATION

16.1 Other Information:

**EXTREMELY FLAMMABLE!** Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. **KEEP OUT OF REACH OF CHILDREN.** 

16.2 Terms & Definitions:

Please see last page of this MSDS.

16.3 Disclaimer

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $O \cdot P \cdot I$ 

16.5 Prepared by:

ShipMate, Inc. PO Box 787 Sisters, OR 97759-0787 USA Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700

e-mail: shipmate@shipmate.com



## **MATERIAL SAFETY DATA SHEET**

Page 10 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date:

08/03/2011

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number	
		_

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

#### FIRST AID MEASURES:

TIKST AID MI	LAJURES.
CPR	Cardiopulmonary resuscitation - method in which a person whose
	heart has stopped receives manual chest compressions and breathing
	to circulate blood and provide oxygen to the body.


#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:







#### OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

#### FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion in air with no
Temperature	other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that
	will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume,
	that will explode or ignite in the presence of an ignition source

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>lo</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	<b>(</b>	(8)		(1)	<b>®</b>		R
Α	В	O	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

		M	*			×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			$\Leftrightarrow$		<b>(4)</b>
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment