MATERIAL SAFETY DATA SHEET

Page 1 of 4

SECTION I Chemical Product and Company Identification

Trade Name Appearing on Label: Spritz Dry Chemical Family:Toiletries

Manufacturer/Distributor/Importers: Orly International, Inc.

7710 Haskell Ave Van Nuys, CA 91406

Emergency Phone: (800) 424-9300 Prepared By: Helga Melger Business Phone: (818) 994-1001 Date prepared: 5/07/99

Revised By: Amy Chang
Revised on: 5/6/2006

Poison Control Center - CHEMTREC: (800) 424-9300

Poison Control Center - CHEMTREC International: (703)527-3887

SECTION II Potentially Hazardous Ingredients Exposure Limits in Air **Chemical Identity** % CAS Number OSHA (PEL) ACGIH (TLV) Other 68 - 83 Alcohol Denat. 64-17-5 750 ppm n/a 750 ppm 16 - 19 67-64-1 n/a n/a Acetone n/a

SECTION III Hazard Identification

HMIS Rating Scale: 0 = Minimal 1 = Slight 2 = Moderate 4 = Severe

This Products Rating: Health: 1 Flammability: 3 Reactivity: 0

Material Appearance: clear colorless liquid

Primary Route of Entry: Inhalation X Skin X Ingestion X

Ingredient(s) Listed as Cancer Causing Agents?:

NTP - no LARC Monographs - no OSHA - no

Target Organs Affected: none

Short Term Effects:

Inhalation: may cause dizziness if inhaled for a prolonged time

Eyes: may cause stinging if product gets into open eyes.

Skin: may cause dry skin if exposed repeatedly and over a prolonged period of time.

Signs and Symptoms of Over-Exposure: may cause dizziness

Medical Conditions Generally Aggravated by Exposure: none known

Page 2 of 4 Spritz Dry

SECTION IV First Aid Measures

Eye Contact: Flush eyes with large amounts of warm water.

Skin Contact: Wash with soap and water.

Inhalation: If dizziness occurs, remove person to fresh air.

Ingestion: Induce vomitting

SECTION V Fire Fighting Measures

Flash Point: Ethyl Acetate - + 7.2°C

Flammable Limits in Air % - LEL: 1, UEL: 13

Extinguishing Media: Dry Chemical X Water Spray X

> Carbon Dioxide _ Foam _

Fire Fighting Procedure: Dowse with plenty of water

SECTION VI Accidental Release Measures

Collect with absobent material and place into trash container. Spill & Leak Procedures:

SECTION VII Handling and Storage

Use a fan or exhaust when handling open containers. Handling:

Storage: Store at room temperature. Keep containers closed when not in use.

SECTION VIII Exposure Controls and Personal Protection

Use a fan or exhaust when working with open containers. Keep away from Heat and open flame.

SECTION IX Physical and Chemical Properties

Water Solubility: Miscible Specific Gravity: (H2O = 1): 0.85 80 - 0.84

Appearance: Clear, colorless Boiling Range: 58 - 75°C

Physical Form: liquid Melting Point: n/a %/Wt. Volutiles: 94 - 99 % Vapor Pressure (mm Hg): NE

рН: 5 - 6 Vapor Density: NE

Odor: Solvent & floral fragrance Evaporation Rate: (Acetone = 1) 1 Flashpoint:(Acetone) -18 °C, CC

Spritz Dry page 3 of 4

SECTION X Stability and Reactivity

Chemical Stability: This product is stable under the recommended storage conditions.

Conditions to avoid: Storage in temperatures above 35 C.

Contact with Materials to avoid: n/a

Hazardous Decomposition Products: will not occur

Hazardous Polymerization: will not occur.

SECTION XI Toxicological Information

LD50(Oral Rat) LC50 (Inhal. Rat)

n/a n/a

Ingestion: May cause headache

Eyes: This product may be a temporary eye irritant if it gets into the open eye.

Dermal: May cause dry skin if exposed repeatedly and over a prolonged time.

Inhalation May cause dizziness if exposed for a prolonged time

Overexposure: all of the above

Chronic Effects: n/a

Carcinogenity: Not listed as a carcinogen by IARC, NTP, OSHA, or ACGIH

Target Organs: n/a

SECTION XII Ecological Information

Ecotoxicity none

SECTION XIII Disposal Considerations

Waste Dosposal: Dispose of absorbed material in accordance with local, state and federal regulations.

SECTION XIV Transport Information

Road Transport: Maritime Transport:

UN Number: 1263 Class: ORM-D Packaging Group: Class: none 3 Label: ORM-D Packaging Group: Ш **UN Number:** Label: 3 none

Air Transport:

UN No. ID8000 Class: 9 Packaging Group: III

Packaging instr.: 910 (passenger)

Spritz Dry page 4 of 4

SECTION XV Regulatory Information

Labelling:

Symbol: F

Indication of Danger: Flammable

Risk Phrases: Flammable

SECTION XVI Other Information

IMPORTANT NOTICE: The information presented herein is based on experimental data submitted by the manufacturers of the raw materials and is considered scientifically correct, however, no warrant or representation, express or implied, is made as to the accuracy or suitability of this information for application to the purchaser's intended purpose or for consequences of its use. Use these materials only as directed. If you have any questions regarding the proper interoperation of this sheet or the meaning of any terms used, we strongly urge you to speak with your physician. For further information concerning product safety and proper use, call the number listed on the front of the MSDS.

These Products Are Designed and Formulated for Professional Salon Use.

They Must be Used with Adequate Ventilation and in Accordance with Manufacturers Instructions.

Abbreviations Used:

NE = Not Established
NKn = Not Known
n/a = Not Applicable
C = Ceiling Limit
TS = Trade Secret
EST = Estimated

N/DA = No Data Available NTP = National Toxicology Program

IRAC = International Agency for Research on Cancer CHEMTREC = Chemical Transportation Emergency Center OSHA = Occupational Safety and Health Administration IPA = Isopropyl Alcohol (Rubbing Alcohol) mm Hg = Millimeters of Mercury

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

STEL = Short Term Exposure Limit

NEGL = Negligible NF = None Found

CAS = Chemical Abstract Service Number

NR = Not Required